

Title (en)

Slip mechanism for use in a timepiece.

Title (de)

Frikionskupplung für Uhren.

Title (fr)

Dispositif d'accouplement à friction pour pièces d'horlogerie.

Publication

EP 0369704 A2 19900523 (EN)

Application

EP 89311708 A 19891113

Priority

JP 14843988 D 19881115

Abstract (en)

A slip mechanism for use in a timepiece comprising a shaft member (20, 20-a, 20-b) made of metallic material; a pinion (22) which is fixed to a first portion (20-b) of the shaft member (20, 20-a, 20-b); and a toothed wheel (21) made of synthetic resin material, the toothed wheel (21) being drivingly connected to a second portion (20-a) of the shaft member (20, 20-a, 20-b) so as to permit rotation of the toothed wheel (21) to be transmitted therefrom to the shaft member (20, 20-a, 20-b) and also to permit slip to occur therebetween characterised in that the pinion (22) is made of synthetic resin material and that the second portion (20-a) of the shaft member (20, 20-a, 20-b) is an integral portion thereof which frictionally engages the toothed wheel (21).

IPC 1-7

G04B 11/00; G04B 13/02; G04B 27/04

IPC 8 full level

G04B 11/00 (2006.01); **G04B 13/02** (2006.01); **G04B 27/04** (2006.01)

CPC (source: EP)

G04B 11/001 (2013.01); **G04B 13/023** (2013.01); **G04B 27/04** (2013.01)

Cited by

WO2013087398A1; GB2266358A; FR2690256A1; EP2605080A1; CN103998996A; US9323221B2; JP2015505962A

Designated contracting state (EPC)

CH DE FR GB LI

DOCDB simple family (publication)

EP 0369704 A2 19900523; EP 0369704 A3 19910206

DOCDB simple family (application)

EP 89311708 A 19891113