

Title (en)

DRAINAGE FITTING FOR A TILED FLOOR

Publication

EP 0371068 B1 19910619 (DE)

Application

EP 88907040 A 19880712

Priority

- DE 3742549 A 19871216
- DE 3804596 A 19880213

Abstract (en)

[origin: US4978250A] PCT No. PCT/EP88/00627 Sec. 371 Date Aug. 15, 1989 Sec. 102(e) Date Aug. 15, 1989 PCT Filed Jul. 12, 1988 PCT Pub. No. WO89/05889 PCT Pub. Date Jun. 29, 1989. The faces (33) of the plate into which the gully is cast, are extended all around by lattices (40) of glass fiber. These form a compound with the subsequently poured plaster floor so that a tension-proof connection is ensured when the tiles are fastened by an adhesive or mortar. According to a preferred embodiment, the plate may additionally be anchored in the plaster floor by reinforcement wire meshes (41) cast into said plate.

IPC 1-7

E03F 5/04

IPC 8 full level

E03F 5/04 (2006.01)

CPC (source: EP US)

E03F 5/0407 (2013.01 - EP US); **E03F 5/0409** (2013.01 - EP US); **E03F 2005/0413** (2013.01 - EP US); **Y10T 137/6988** (2015.04 - EP US)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI

DOCDB simple family (publication)

US 4978250 A 19901218; DE 3863357 D1 19910725; EP 0371068 A1 19900606; EP 0371068 B1 19910619; ES 2011928 A6 19900216; WO 8905889 A1 19890629

DOCDB simple family (application)

US 39946389 A 19890815; DE 3863357 T 19880712; EP 8800627 W 19880712; EP 88907040 A 19880712; ES 8803806 A 19881215