

Title (en)

Wire matrix print head of the clapper type.

Title (de)

Matrixnadeldruckkopf der Klappankerbauart.

Title (fr)

Tête d'impression matricielle à aiguilles du type à armature battante.

Publication

**EP 0371183 B1 19940518 (DE)**

Application

**EP 88730266 A 19881201**

Priority

EP 88730266 A 19881201

Abstract (en)

[origin: EP0371183A1] A wire matrix print head of the clapper type has a plurality of systems which are composed in each case of a pair of magnet yoke limbs (2), an electromagnet coil (3), a clapper (4) and a printing needle (1) and, furthermore, have an electromagnet coil carrier (13) which is made of iron sinter or precision casting and, together with a base plate and the pairs of magnet yoke limbs (2), forms a one-piece component. <??>In order to achieve anchor guiding, in particular for low-number systems (such as, for example, nine needles) without using up magnetic energy, in which the individual clappers (4) are mounted with extreme precision, it is proposed that the electromagnet coil carrier (13) has individual magnet yoke limbs (2a) arranged radially on the outside which are each aligned onto a needle contact point (8) or onto a needle attachment point (8b), that the radially inner magnet yokes are shaped to form a closed, circular or polygonal ring (17), and that the clappers (4) are each assigned guide means (18) which are coordinated with the swivel movements of the clappers and interact with receiving means (19) on the closed ring (17). <IMAGE>

IPC 1-7

**B41J 2/275**; **B41J 2/235**

IPC 8 full level

**B41J 2/235** (2006.01); **B41J 2/275** (2006.01)

CPC (source: EP US)

**B41J 2/235** (2013.01 - EP US); **B41J 2/275** (2013.01 - EP US)

Cited by

CN102744974A; DE102004028904A1; DE102004028904B4

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)

**EP 0371183 A1 19900606**; **EP 0371183 B1 19940518**; AT E105782 T1 19940615; DE 3889662 D1 19940623; JP H02188266 A 19900724; US 5009529 A 19910423

DOCDB simple family (application)

**EP 88730266 A 19881201**; AT 88730266 T 19881201; DE 3889662 T 19881201; JP 31046189 A 19891129; US 44375489 A 19891130