

Title (en)  
Web forming method and apparatus.

Title (de)  
Verfahren und Vorrichtung zur Herstellung von Bahnen.

Title (fr)  
Procédé et dispositif de formation de bandes continues.

Publication  
**EP 0371786 A2 19900606 (EN)**

Application  
**EP 89312431 A 19891129**

Priority  
FI 885606 A 19881201

Abstract (en)  
A method for forming a paper or paperboard web from a fibrous material in the wire section of a paper making machine or equivalent machine comprising a bottom wire loop (2;102) with the main portion of its top run being horizontal or substantially horizontal, and a top wire loop (10;110) working in conjunction with the bottom wire loop; wherein in the method fibre slurry coming out of the headbox (1;101) of the paper making machine is fed to the first part (2a; 102a) of the top run of said bottom wire loop (2;102), which forms the first dewatering zone after which the partly formed fibre layer is led to the second dewatering zone, in the area of which said top wire loop (10;110) moves to cover said partly formed fibre layer in such a way that water removal from the fibre layer continues at least in two stages in the area of said second dewatering zone, whereupon the top wire loop (10;110) is separated from the nearly formed web (W) that is led to follow the run of the bottom wire loop (2;102) forward to the next processing stages of the web (W), wherein the method is characterized in that in the single-wired dewatering zone (2a;102a), after the initial water removal is carried out through the bottom wire (2;102), water removal through the bottom wire (2;102) is prevented by means of an element group (9; 109) operating in contact with the inner surface of the horizontal top run of the bottom wires; that in said water-removal prevention area water is removed from the web (W) through the top wire in the first stage or stages of the double-wired second dewatering zone, which stages comprise a relatively long, planar wire table extending from the headbox to the forming roll (6 in Fig. 1), or from the headbox to the last supporting element (109 in Fig. 2); and that after the first dewatering stage or stages of the double-wired zone water is removed in a curved double-wired dewatering zone (b) (Fig. 1) or zones (Ro, C) (Fig. 2), after which the web (W) is led to follow the bottom wire (2;102).

IPC 1-7  
**D21F 1/48**; **D21F 9/00**

IPC 8 full level  
**D21F 1/00** (2006.01); **D21F 1/48** (2006.01); **D21F 3/00** (2006.01); **D21F 9/00** (2006.01)

CPC (source: EP KR)  
**D21F 1/00** (2013.01 - KR); **D21F 1/48** (2013.01 - EP); **D21F 3/00** (2013.01 - EP); **D21F 9/003** (2013.01 - EP)

Cited by  
EP1619300A1; EP1676951A1; US5552021A; EP0475921A1; US5573643A; DE19680959B4; EP1116822A3; DE4026953A1; DE4330546A1; DE4141607A1; US5507918A; US6071381A; DE4219292A1; US6322669B1; WO9511338A1; WO9110775A1; WO9307336A1; US6716315B2; US7189309B2; US8758571B2; WO2012087214A1; EP3165642B1

Designated contracting state (EPC)  
AT DE ES FR GB IT SE

DOCDB simple family (publication)  
**EP 0371786 A2 19900606**; **EP 0371786 A3 19901122**; CA 2004123 A1 19900601; CN 1045828 A 19901003; FI 885606 A0 19881201; FI 885606 A 19900602; JP H02191792 A 19900727; KR 900010147 A 19900706

DOCDB simple family (application)  
**EP 89312431 A 19891129**; CA 2004123 A 19891129; CN 89109546 A 19891201; FI 885606 A 19881201; JP 31087289 A 19891201; KR 890017916 A 19891201