

Title (en)
SEWING MACHINE

Publication
EP 0371922 B1 19930728 (FR)

Application
EP 89810885 A 19891120

Priority
CH 443188 A 19881129

Abstract (en)
[origin: EP0371922A1] The fabric transport claw (17) of the sewing machine is equipped with a spring wire (21) bent at (22) and passing through a hole of a block (23). When the claw (17) is in the high position, the block (23) comes up against the plate (18), thus lowering the end (24) of the wire (21) in order to exert tension on the lower thread (8) of the stitched seam. When the transport claw descends, the wire (21) resumes its normal position, that is to say its end (24) moves upwards relative to the claw (17), and the thread (8) is thus relieved. <IMAGE>

IPC 1-7
D05B 57/14

IPC 8 full level
D05B 53/00 (2006.01); **D05B 57/14** (2006.01); **D05B 61/00** (2006.01); **D05B 63/00** (2006.01)

CPC (source: EP KR US)
D05B 55/00 (2013.01 - KR); **D05B 57/143** (2013.01 - EP US); **D05B 61/00** (2013.01 - EP US)

Designated contracting state (EPC)
DE ES FR GB IT SE

DOCDB simple family (publication)
EP 0371922 A1 19900606; EP 0371922 B1 19930728; AU 4559789 A 19900607; AU 621420 B2 19920312; BR 8906016 A 19900619; CA 2004054 A1 19900529; CH 676478 A5 19910131; CN 1024207 C 19940413; CN 1043168 A 19900620; DD 289783 A5 19910508; DE 68907867 D1 19930902; DE 68907867 T2 19940127; ES 2042064 T3 19931201; JP H02182289 A 19900716; KR 900008095 A 19900602; PT 92418 A 19900531; PT 92418 B 19950809; RU 1834935 C 19930815; US 5048438 A 19910917; ZA 898422 B 19900627

DOCDB simple family (application)
EP 89810885 A 19891120; AU 4559789 A 19891128; BR 8906016 A 19891129; CA 2004054 A 19891128; CH 443188 A 19881129; CN 89108396 A 19891102; DD 33492989 A 19891128; DE 68907867 T 19891120; ES 89810885 T 19891120; JP 30494489 A 19891127; KR 890017304 A 19891128; PT 9241889 A 19891127; SU 4742539 A 19891121; US 43946889 A 19891121; ZA 898422 A 19891106