

Title (en)

HEAT-SENSITIVE RECORDING MATERIAL, ITS MANUFACTURING METHOD IMAGE FORMING PROCESS

Publication

**EP 0372800 A3 19910605 (EN)**

Application

**EP 89312373 A 19891128**

Priority

- JP 8772389 A 19890406
- JP 30518788 A 19881202
- JP 30531188 A 19881202
- JP 30859688 A 19881206

Abstract (en)

[origin: EP0372800A2] A heat sensitive recording material is disclosed. The material comprises an image receiving layer and a colorant layer, wherein the image receiving layer is adhered to the colorant layer so firmly that the image receiving layer can be separated from the colorant layer with a peeling force of 0.1 to 1000 g/mm at an angle of 180 DEG after forming an image on the image receiving layer.

IPC 1-7

**B41M 5/38**

IPC 8 full level

**B41M 5/26** (2006.01); **B41M 5/382** (2006.01); **B41M 5/40** (2006.01); **B41M 5/41** (2006.01); **B41M 5/42** (2006.01); **B41M 5/44** (2006.01)

CPC (source: EP)

**B41M 5/38207** (2013.01); **B41M 5/41** (2013.01); **B41M 5/42** (2013.01); **B41M 5/443** (2013.01)

Citation (search report)

- [X] EP 0249195 A2 19871216 - CANON KK [JP]
- [A] GB 2044473 A 19801015 - MINNESOTA MINING & MFG
- [X] PATENT ABSTRACTS OF JAPAN vol. 12, no. 164 (M-698)(3011) 18 May 1988, & JP-A-62 280084 (DAINIPPON PRINTING COMPANY LIMITED) 04 December 1987,
- [XP] PATENT ABSTRACTS OF JAPAN vol. 14, no. 13 (M-918)(3956) 11 January 1990, & JP-A-01 258989 (UNION KEMIKAA K.K.) 16 October 1989,

Cited by

EP0911695A1

Designated contracting state (EPC)

DE GB IT

DOCDB simple family (publication)

**EP 0372800 A2 19900613**; **EP 0372800 A3 19910605**; **EP 0372800 B1 19960306**; DE 68925870 D1 19960411

DOCDB simple family (application)

**EP 89312373 A 19891128**; DE 68925870 T 19891128