

Title (en)  
Pouring container with a self-draining feature.

Title (de)  
Behälter mit Ausgiesstülle und Tropfenrückführung.

Title (fr)  
Récipient verseur récupérateur.

Publication  
**EP 0373980 A1 19900620 (FR)**

Application  
**EP 89403097 A 19891109**

Priority  
FR 8816462 A 19881214

Abstract (en)  
Pouring container intended to receive a liquid product and comprising an outlet tube (1) having an axis and surrounded by a sleeve constituting the neck of the container and is connected to the said sleeve (2) by a surface (3) which is oblique relative to the axis of the outlet tube (1) and has, when the axis of the outlet tube (1) is vertical, a low point in the vicinity of which an orifice (4) is made, the free end of the said outlet tube (1) being shaped so as to form a pouring spout (6), over a fraction of its periphery contained in a dihedron whose edge (6a) is the axis of the outlet tube (1) and whose angle is less than 180 DEG , the low point of the recovery surface (3) being in the dihedron opposite that which contains the pouring spout (6). The outlet tube (1) carries, over the part of its outer wall contained in the dihedron delimiting the pouring spout (6), fins (7, 8) which are substantially parallel to its axis. <IMAGE> <IMAGE> <IMAGE>

Abstract (fr)  
Récipient verseur, destiné à recevoir un produit liquide et comportant un tube de sortie (1) ayant un axe et entouré d'un manchon constituant le goulot du récipient et est relié audit manchon (2) par une surface (3) oblique par rapport à l'axe du tube de sortie (1) présentant, lorsque l'axe du tube de sortie (1) est vertical, un point bas au voisinage duquel est ménagé un orifice (4), l'extrémité libre dudit tube de sortie (1) étant conformée pour constituer un bec verseur (6), sur une fraction de sa périphérie comprise dans un dièdre dont l'arête (6a) est l'axe du tube de sortie (1) et dont l'angle est inférieur à 180 °, le point bas de la surface récupératrice (3) étant dans le dièdre opposé à celui qui contient le bec verseur (6). Le tube de sortie (1) porte, sur la partie de sa paroi extérieure comprise dans le dièdre délimitant le bec verseur (6), des ailettes (7, 8) sensiblement parallèles à son axe.

IPC 1-7  
**B65D 23/06**; **B65D 47/06**; **B65D 47/40**

IPC 8 full level  
**B65D 23/06** (2006.01); **B65D 47/06** (2006.01); **B65D 47/40** (2006.01)

CPC (source: EP)  
**B65D 23/06** (2013.01); **B65D 47/06** (2013.01); **B65D 47/40** (2013.01)

Citation (search report)  
• [A] EP 0109704 A1 19840530 - PROCTER & GAMBLE [US]  
• [A] FR 1539317 A 19680913 - SANNER KG FRIEDR  
• [A] BE 663671 A 19651110

Cited by  
CN106628504A; JP2017074950A

Designated contracting state (EPC)  
BE DE ES FR GB IT NL

DOCDB simple family (publication)  
**EP 0373980 A1 19900620**; **EP 0373980 B1 19930414**; DE 68906004 D1 19930519; FR 2640238 A1 19900615; FR 2640238 B1 19910510

DOCDB simple family (application)  
**EP 89403097 A 19891109**; DE 68906004 T 19891109; FR 8816462 A 19881214