

Title (en)

Code break mechanism for stacking apparatus.

Title (de)

Vorrichtung zur codifizierten Unterbrechung einer Stapleinrichtung.

Title (fr)

Mécanisme de discontinuité par code pour appareil d'empilage.

Publication

**EP 0376463 A2 19900704 (EN)**

Application

**EP 89311980 A 19891120**

Priority

US 29148488 A 19881228

Abstract (en)

A code break mechanism is preferably employed in a stacker apparatus. The stacker apparatus has a support housing, a deck (31) fixably mounted to and supported by the housing, a registration wall (145) fixed to the housing and extending generally perpendicular to the deck. A deflector plate (202) is pivotally mounted in an opening (204) in the registration wall. A rotary solenoid (216) in communication with a linkage train (206, 208, 220) causes the deflector plate (202) to be selectively positionable from a first position coplanar with the registration wall (145) to a second position pivotally displaced from the registration wall.

IPC 1-7

**B65H 33/10**

IPC 8 full level

**B65H 33/08** (2006.01); **B65H 33/10** (2006.01)

CPC (source: EP)

**B65H 33/10** (2013.01); **B65H 2301/42144** (2013.01); **B65H 2701/1916** (2013.01)

Cited by

FR2727954A1; EP2041014A4

Designated contracting state (EPC)

BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0376463 A2 19900704**; **EP 0376463 A3 19910320**; **EP 0376463 B1 19940803**; AU 4432389 A 19900705; AU 634498 B2 19930225; CA 2002215 A1 19900628; CA 2002215 C 19990302; DE 68917278 D1 19940908; DE 68917278 T2 19941124; JP 2706161 B2 19980128; JP H02215651 A 19900828

DOCDB simple family (application)

**EP 89311980 A 19891120**; AU 4432389 A 19891103; CA 2002215 A 19891103; DE 68917278 T 19891120; JP 31226089 A 19891130