

Title (en)

Decanter with a vibration upsetting component

Title (de)

Dekanter mit einem insoweit schwingungsentkoppelten Bauteil

Title (fr)

Décanteur à élément de construction suspendu élastiquement

Publication

EP 0376919 B1 19970409 (DE)

Application

EP 90100036 A 19900102

Priority

- DE 3844406 A 19881230
- DE 3844407 A 19881230

Abstract (en)

[origin: EP0376919A2] Decanter for separating suspensions, having a machine bed, a drum rotatably supported on the latter, a worm mounted rotationally in the latter with a differential speed of rotation, a transmission connected between the drum and the worm, a drive motor connected to the transmission or to the rotation unit consisting of drum and worm via a torque transmission device and also mounted so as to be supported on the machine bed, and having feed lines and discharge lines and, if appropriate, auxiliary units which are also mounted on the machine bed. Such a decanter system forms, connected over the machine bed, a mass system in which critical natural oscillations are to be as far as possible avoided or damped. For this purpose, the decanter system is constructed in such a way that at least one of the components and/or auxiliary units mounted on the machine bed is decoupled from the other components mounted on the machine bed in at least one direction extending with a component directed parallel to the axis of rotation of the decanter, with the exception of the direction of the drive torque transmission, by means of elastic mounting and/or is coupled to the other components by means of a damping element.

IPC 1-7

B04B 1/20; B04B 9/12

IPC 8 full level

B04B 1/20 (2006.01); B04B 9/12 (2006.01)

CPC (source: EP US)

B04B 1/2016 (2013.01 - EP US); B04B 9/12 (2013.01 - EP US)

Designated contracting state (EPC)

DE DK FR GB IT

DOCDB simple family (publication)

EP 0376919 A2 19900704; EP 0376919 A3 19910502; EP 0376919 B1 19970409; DE 59010695 D1 19970515; DK 0376919 T3 19970428;
US 5120298 A 19920609

DOCDB simple family (application)

EP 90100036 A 19900102; DE 59010695 T 19900102; DK 90100036 T 19900102; US 45963690 A 19900102