

Title (en)  
KEY FOR A CYLINDER LOCK

Publication  
**EP 0377135 A3 19910508 (DE)**

Application  
**EP 89122735 A 19891209**

Priority  
DE 8900042 U 19890104

Abstract (en)  
[origin: EP0377135A2] A cylinder-lock key (6) for a lock-cylinder group consisting of at least two lock cylinders (1,2) equipped with a different number of pin tumblers (3), especially for lock installations equipped therewith, is provided with at least two key abutments (7,8) which are located at axially different points on the key (6) and limit different insertion depths and of which the first (7) is arranged in the vicinity of the key head (6') and limits the insertion depth by striking against the end face (11') of the lock-cylinder core (11). In order to make do with lock-cylinder cores (11) changed only in respect of the number of pin tumblers, the second key abutment (8) is arranged at an axial distance from the key tip (6<IV>) and rotationally offset, as seen in the axial direction of the key (6), or longitudinally adjustably in relation to the first key abutment (7) located near the key head. <IMAGE>

IPC 1-7  
**E05B 19/04**; **E05B 27/00**

IPC 8 full level  
**E05B 19/00** (2006.01); **E05B 19/04** (2006.01); **E05B 19/06** (2006.01); **E05B 27/00** (2006.01); **E05B 27/04** (2006.01)

CPC (source: EP)  
**E05B 19/00** (2013.01)

Citation (search report)  
• [X] GB 1428966 A 19760324 - WILMOT BREEDEN LTD  
• [X] US 3942347 A 19760309 - COLEMAN MARVIN WITHAM  
• [A] US 2199165 A 19400430 - SMITH BERNARD C

Cited by  
US5355702A; FR2716693A1; EP0947649A1; ES2136478A1; GB2366595A; EP1270852A3; FR2777034A1; FR2670820A1; AT513606A4; AT513606B1; EP0637663A1; US2016145896A1; US10316547B2; SE2350935A1; SE2350936A1; WO2024041845A1

Designated contracting state (EPC)  
BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**DE 8900042 U1 19890302**; DE 58905976 D1 19931125; EP 0377135 A2 19900711; EP 0377135 A3 19910508; EP 0377135 B1 19931020

DOCDB simple family (application)  
**DE 8900042 U 19890104**; DE 58905976 T 19891209; EP 89122735 A 19891209