

Title (en)

CONNECTION FOR TWO CONSTRUCTION ELEMENTS

Publication

EP 0377819 A3 19910918 (DE)

Application

EP 89122121 A 19891130

Priority

DE 3900326 A 19890107

Abstract (en)

[origin: EP0377819A2] An elastically bending connection for two construction elements is produced as a plastic moulded part which has an elastically bending shank (16). This shank (16) preferably has two constrictions (23, 24) in the cross-section, arranged one behind the other in the axial direction and displaced through 90 DEG in the radial direction, each of which are constructed as notches which are introduced from two sides. The shank (16) thus represents a connection having high strength in the axial direction and a low resistance to a radially acting bending force. The connection can connect two parts together, without any additional aligning work. <IMAGE>

IPC 1-7

H01H 3/46

IPC 8 full level

F15B 15/28 (2006.01); **F16B 7/00** (2006.01); **F16C 11/12** (2006.01); **F16D 3/74** (2006.01); **G01B 7/00** (2006.01); **G01B 7/02** (2006.01); **H01H 3/38** (2006.01); **H01H 3/46** (2006.01)

CPC (source: EP)

H01H 3/38 (2013.01); **H01H 2003/105** (2013.01)

Citation (search report)

- [X] US 3290949 A 19661213 - FRANK SAMET
- [X] US 3405539 A 19681015 - AKIRA TANAKA
- [X] FR 1411175 A 19650917 - ERMAT
- [Y] US 4473950 A 19841002 - FINN ALBERT E [US], et al

Cited by

BE1019843A3; CN109253687A; CN105097312A; GB2432000A; GB2432000B

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0377819 A2 19900718; **EP 0377819 A3 19910918**; **EP 0377819 B1 19950510**; DE 3900326 A1 19900712; DE 58909227 D1 19950614; JP H02109020 U 19900830; JP H085376 Y2 19960214

DOCDB simple family (application)

EP 89122121 A 19891130; DE 3900326 A 19890107; DE 58909227 T 19891130; JP 4390 U 19900105