

Title (en)  
Manipulating device for piecing a yarn

Title (de)  
Handhabungsgerät zum Garnansetzen

Title (fr)  
Mode d'opération pour rattacher le fil

Publication  
**EP 0377888 B1 19960717 (DE)**

Application  
**EP 89123852 A 19891222**

Priority  
• CH 112289 A 19890328  
• CH 112189 A 19890328  
• CH 105589 A 19890322  
• CH 485288 A 19881231

Abstract (en)  
[origin: WO9007599A1] To repair thread breakage in a ring spinning machine, the thread to be joined is guided toward the drawing rollers along a predetermined path above the spindle. The thread is threaded through a guide eye and, if necessary, through an antiballooning ring. The preprogrammed movements of the thread are guided by a manipulating device fitted with servo shafts (172, 178, 188).

IPC 1-7  
**D01H 15/013**

IPC 8 full level  
**D01H 15/00** (2006.01); **D01H 15/013** (2006.01)

CPC (source: EP)  
**D01H 15/00** (2013.01); **D01H 15/013** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0382943 A1 19900822; EP 0382943 B1 19950913**; AT E127868 T1 19950915; AT E140490 T1 19960815; DE 58909434 D1 19951019; DE 58909703 D1 19960822; EP 0377888 A1 19900718; EP 0377888 B1 19960717; JP H03503912 A 19910829; JP H03504146 A 19910912; WO 9007598 A1 19900712; WO 9007599 A1 19900712

DOCDB simple family (application)  
**EP 89123853 A 19891222**; AT 89123852 T 19891222; AT 89123853 T 19891222; DE 58909434 T 19891222; DE 58909703 T 19891222; EP 8901603 W 19891222; EP 8901604 W 19891222; EP 89123852 A 19891222; JP 50103590 A 19891222; JP 50173189 A 19891222