

Title (en)

Method of applying a mortar material to a surface.

Title (de)

Verfahren zum Auftragen von Mörtel auf eine Formfläche.

Title (fr)

Méthode pour appliquer un mortier sur une surface.

Publication

**EP 0378437 A2 19900718 (EN)**

Application

**EP 90300376 A 19900112**

Priority

GB 8900736 A 19890113

Abstract (en)

Simulated stone products are prepared by spraying a mortar material, in a blast of compressed air, into a mould by means of a gun 10, 14, 16, to which the mortar material is fed via a lateral inlet 12 by a peristaltic pump. Compressed air is supplied to an axially extending pipe 18 within the body 10 of the gun, the pipe 18 terminating, within the body 10, just short of a nozzle 16 from which the mortar spray is ejected. The mortar is effectively "atomised" in the spray, so that individual aggregate particles, such as sand grains, coated with cement, are hurled at high speed, in the spray, against the mould surface or against the previously deposited particle to form a densely packed aggregate layer which, in curing, de-moulding and surface etching or abrasion, closely simulates the appearance of natural stone. The apparatus and method disclosed allow, inter alia, products which are relatively thin and light, and are yet strong, to be produced economically.

IPC 1-7

**B05B 7/04; B28B 1/32; B28B 11/08; B28B 23/02; E04F 21/12**

IPC 8 full level

**B28B 1/32 (2006.01); B28B 11/08 (2006.01); E04F 21/12 (2006.01)**

CPC (source: EP)

**B28B 1/32 (2013.01); B28B 11/0818 (2013.01); E04F 21/12 (2013.01)**

Cited by

EP0847808A1; US5467923A; FR2676020A1; CN107724651A; FR3038331A1; US10315956B2; WO2015134978A1; US11040463B2; WO2017001734A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0378437 A2 19900718; EP 0378437 A3 19910116; EP 0378437 B1 19940518;** AT E105904 T1 19940615; DE 69008873 D1 19940623; DE 69008873 T2 19950105; GB 8900736 D0 19890308

DOCDB simple family (application)

**EP 90300376 A 19900112;** AT 90300376 T 19900112; DE 69008873 T 19900112; GB 8900736 A 19890113