

Title (en)  
ICR ION TRAP.

Title (de)  
ICR-IONENFALLE.

Title (fr)  
PIEGE A IONS ICR.

Publication  
**EP 0378648 B1 19950524 (DE)**

Application  
**EP 89907696 A 19890628**

Priority  

- DE 3821998 A 19880630
- EP 8900751 W 19890628

Abstract (en)  
[origin: WO9000309A1] An ICR ion trap has side plates (1) parallel to an axis (Z) and end plates (5, 6) perpendicular to the axis (Z). A voltage source (7) makes it possible to apply capture potentials to the side and end plates. Additional electrode plates (8, 9) to which capture potentials of opposite polarity to the end plates can be applied are arranged at a distance from the end plates, thereby forming an outer space in which ions of opposite sign are captured. After analysis and elimination of the ions present in the inner chamber, the ions of opposite sign are captured in the inner chamber and analysed. It is also possible to observe recombination reactions between ions of opposite sign.

IPC 1-7  
**H01J 49/38**

IPC 8 full level  
**G01N 27/62** (2006.01); **G21K 1/00** (2006.01); **H01J 49/38** (2006.01)

CPC (source: EP US)  
**H01J 49/38** (2013.01 - EP US)

Citation (examination)  
EP 0215011 A1 19870325 - NICOLET INSTRUMENT CORP [US]

Designated contracting state (EPC)  
CH DE FR GB LI

DOCDB simple family (publication)  
**WO 9000309 A1 19900111**; DE 3821998 A1 19900104; DE 3821998 C2 19911212; DE 58909253 D1 19950629; EP 0378648 A1 19900725;  
EP 0378648 B1 19950524; JP H03501187 A 19910314; JP H0668969 B2 19940831; US 4982087 A 19910101; US 5089702 A 19920218

DOCDB simple family (application)  
**EP 8900751 W 19890628**; DE 3821998 A 19880630; DE 58909253 T 19890628; EP 89907696 A 19890628; JP 50722489 A 19890628;  
US 46093890 A 19900221; US 61248190 A 19901212