

Title (en)
PRESSER ATTACHMENT DEVICE FOR A SEWING MACHINE

Publication
EP 0378965 B1 19930908 (FR)

Application
EP 89810850 A 19891108

Priority
CH 443788 A 19881130

Abstract (en)
[origin: EP0378965A1] In this device, a rocker lever (70) carrying a presser foot (71) can be guided, by a suitable actuating device, from a low position, in which the foot (71) is laid onto the material to be sewn, into a high position distant from this. <??>For this purpose, the lever (70) is equipped with rolling members (70c) resting on guide ramps (72a), these members and/or these ramps having such a profile that, during the displacement of the presser foot between its two positions, this foot always follows a vertical path.

IPC 1-7
D05B 19/00; **D05B 29/00**

IPC 8 full level
D05B 29/00 (2006.01); **D05B 29/02** (2006.01)

CPC (source: EP US)
D05B 19/00 (2013.01 - EP US); **D05B 29/02** (2013.01 - EP US)

Cited by
US5143006A; US5205230A

Designated contracting state (EPC)
DE ES FR GB IT SE

DOCDB simple family (publication)
EP 0378965 A1 19900725; **EP 0378965 B1 19930908**; AU 4569989 A 19900607; AU 619062 B2 19920116; BR 8906059 A 19900619; CA 2004066 A1 19900531; CH 677508 A5 19910531; CN 1024026 C 19940316; CN 1043171 A 19900620; DD 296124 A5 19911121; DE 68909031 D1 19931014; DE 68909031 T2 19940421; ES 2045547 T3 19940116; JP H02182287 A 19900716; PT 92427 A 19900531; PT 92427 B 19950809; RU 1834933 C 19930815; US 5042406 A 19910827; ZA 899037 B 19900926

DOCDB simple family (application)
EP 89810850 A 19891108; AU 4569989 A 19891129; BR 8906059 A 19891130; CA 2004066 A 19891128; CH 443788 A 19881130; CN 89109015 A 19891130; DD 33493589 A 19891128; DE 68909031 T 19891108; ES 89810850 T 19891108; JP 30786089 A 19891129; PT 9242789 A 19891128; SU 4742456 A 19891129; US 44332689 A 19891130; ZA 899037 A 19891127