

Title (en)
Curling iron with retractable bristles or teeth.

Title (de)
Lockenstab mit einziehbaren Borsten oder Zinken.

Title (fr)
Fer à friser avec soies ou dents escamotables.

Publication
EP 0379670 B1 19940126 (DE)

Application
EP 89121647 A 19891123

Priority
DE 3902111 A 19890125

Abstract (en)
[origin: JPH02228906A] PURPOSE: To enable withdrawal of a hair winder barrel member without a step of unwinding the hair once wound thereon by manipulating a bristle or sawtooth-like multiple-protrusion adjusting device according to aeration temperatures, with more than one temperature sensing elements of a shape retentive metal provided in an aeration passage. CONSTITUTION: Air 2 is fed from main body 1 to the interior of hair winder barrel member 3 through a heater and a blower, then getting released to the exterior via aeration hole 4. Inside hair wind barrel member 3, adjusting device 5 is installed axially movably, and also serves as holder of bristle 6. The adjusting device 5 is cylindrical and has outlet ports 7 for aeration in its periphery. Bristle 6 is implanted in bundles which are protruding to the exterior from the respective aeration holes 4. The adjusting device 5 is held axially by a thermosensitive elements 8, each of which is made of a shape memory alloy, allowing various shapes such as a U-shape, a coil-like form of a split spring shape to be formed. Preferably, the bristle or sawtooth-like multiple-protrusion holder is formed pivotable, and in this case, the thermosensitive element is preferably formed in a split spring shape.

IPC 1-7
A45D 1/04; **A45D 1/18**; **A45D 20/50**

IPC 8 full level
A45D 2/36 (2006.01); **A45D 1/00** (2006.01); **A45D 1/04** (2006.01); **A45D 1/18** (2006.01); **A45D 20/50** (2006.01)

CPC (source: EP US)
A45D 1/18 (2013.01 - EP US); **A45D 20/50** (2013.01 - EP US)

Cited by
WO9709899A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0379670 A2 19900801; **EP 0379670 A3 19910403**; **EP 0379670 B1 19940126**; AT E100680 T1 19940215; DE 3902111 A1 19900726; DE 58906834 D1 19940310; ES 2050763 T3 19940601; JP 2750927 B2 19980518; JP H02228906 A 19900911; US 4971081 A 19901120

DOCDB simple family (application)
EP 89121647 A 19891123; AT 89121647 T 19891123; DE 3902111 A 19890125; DE 58906834 T 19891123; ES 89121647 T 19891123; JP 33802689 A 19891225; US 46547990 A 19900116