

Title (en)

Developer mix monitoring for replaceable developer stations.

Title (de)

Entwicklermischungssteuerung für austauschbare Entwicklereinheiten.

Title (fr)

Contrôle de mélange de révélateur pour postes de révélateur remplaçables.

Publication

EP 0380626 B1 19940302 (EN)

Application

EP 89908306 A 19890627

Priority

- US 21496788 A 19880705
- US 21597188 A 19880707

Abstract (en)

[origin: WO9000728A1] A toner monitor (125) in an electrostatographic machine is automatically calibrated when a new replaceable development station (10) is loaded into the machine. The detected toner concentration in the development station is used by the monitor as a reference signal against which future readings are compared. The reference signal is reset upon machine power-up to correspond to the detected toner concentration in the development station (10), but only when there is a fresh development station in the machine. Resetting the reference signal only when there is a fresh development station prevents erroneous reference signals which would result if the developer mix concentration was other than perfect at power-down.

IPC 1-7

G03G 15/08

IPC 8 full level

G03G 15/08 (2006.01)

CPC (source: EP)

G03G 15/0849 (2013.01); **G03G 15/0853** (2013.01); **G03G 15/0896** (2013.01)

Cited by

CN100430839C

Designated contracting state (EPC)

DE FR GB NL

DOCDB simple family (publication)

WO 9000728 A1 19900125; DE 68913503 D1 19940407; DE 68913503 T2 19940728; EP 0380626 A1 19900808; EP 0380626 B1 19940302; JP H03501658 A 19910411

DOCDB simple family (application)

US 8902861 W 19890627; DE 68913503 T 19890627; EP 89908306 A 19890627; JP 50801989 A 19890627