

Title (en)  
DEVICE AND METHOD FOR THE DOSED FILLING OF STATIONARY MOULDS

Publication  
**EP 0380758 B1 19930616 (DE)**

Application  
**EP 89119454 A 19891020**

Priority  
DE 3902646 A 19890130

Abstract (en)  
[origin: EP0380758A2] The filling device for the dosed filling of stationary moulds has a base comprising oscillating bodies (2) which are moved relative to one another, taper towards the top, and are arranged at a distance from one another so that a gap (6) corresponding approximately to the openings (7) in the mould (8) arises. Since the filling operation with an appropriately chosen gap width is ended by turning off the oscillating drive (5), the base can be arranged at a distance from the mould (8) such that no wear due to friction can arise. <IMAGE>

IPC 1-7  
**B27N 3/14**; **B27N 5/00**

IPC 8 full level  
**B27N 3/14** (2006.01); **B27N 5/00** (2006.01); **B30B 15/30** (2006.01)

CPC (source: EP)  
**B27N 3/14** (2013.01); **B27N 5/00** (2013.01); **B30B 15/304** (2013.01)

Designated contracting state (EPC)  
AT DE FR GB LU NL

DOCDB simple family (publication)  
**EP 0380758 A2 19900808**; **EP 0380758 A3 19911016**; **EP 0380758 B1 19930616**; AT E90612 T1 19930715; DE 3902646 A1 19900802; DE 58904736 D1 19930722

DOCDB simple family (application)  
**EP 89119454 A 19891020**; AT 89119454 T 19891020; DE 3902646 A 19890130; DE 58904736 T 19891020