

Title (en)

Elongate flexible elements particularly for use as glazing strips.

Title (de)

Längliche flexible Elemente, insbesondere für Verglasungsleisten.

Title (fr)

Éléments oblongs et flexibles en particulier pour pargloses.

Publication

EP 0381425 A2 19900808 (EN)

Application

EP 90300922 A 19900130

Priority

GB 8902188 A 19890201

Abstract (en)

An elongate flexible element for use as a glazing gasket comprises a main body (10) integrally formed with a tear-off strip (15) extending along the length thereof, the tear-off strip being connected to the main body (10) by a zone which may be readily ruptured to enable the strip to be detached from the main body. The effective thickness of the glazing strip may therefore be reduced, if required, by removing the tear-off strip (15). Adjacent the rupturable zone there is integrally formed with the gasket an elongate strip (18) of material which is harder and less flexible than the material of the main body and tear-off strip, so as to facilitate the tearing-off of the strip (15).

IPC 1-7

E06B 3/62

IPC 8 full level

E06B 3/62 (2006.01)

CPC (source: EP)

E06B 3/62 (2013.01); **E06B 2003/6211** (2013.01); **E06B 2003/6223** (2013.01); **E06B 2003/6229** (2013.01); **E06B 2003/6258** (2013.01); **E06B 2003/6273** (2013.01); **E06B 2003/6276** (2013.01)

Cited by

EP1600594A1; CN109356492A; EP1144771A4; JP2013096119A

Designated contracting state (EPC)

AT BE CH DE DK ES FR IT LI NL SE

DOCDB simple family (publication)

EP 0381425 A2 19900808; **EP 0381425 A3 19901107**; GB 2227781 A 19900808; GB 2227781 B 19930127; GB 8902188 D0 19890322; GB 9002097 D0 19900328

DOCDB simple family (application)

EP 90300922 A 19900130; GB 8902188 A 19890201; GB 9002097 A 19900130