

Title (en)

Method for laying an entrenched conduit

Title (de)

Verfahren zur Herstellung einer vergraben Leitung

Title (fr)

Procédé de réalisation d'un conduit enterré

Publication

EP 0381547 B1 19960717 (FR)

Application

EP 90400144 A 19900118

Priority

FR 8900700 A 19890120

Abstract (en)

[origin: EP0381547A1] The subject of the invention is a method for producing an entrenched conduit by assembling a plurality of prefabricated elements on site and the prefabricated elements prepared for carrying out the method. <??>According to the invention, the dimensional and structural characteristics of a plurality of series (I,I') (III, III') of base elements (1) and (II, II') of upper elements (2), corresponding in pairs to identical widths (L) between supports, are predetermined some of the characteristics of form and resistance by varying in each series, subsequently base elements (1) and upper elements (2) are associated in a plurality of ways to form typical sections of the same width (L), for each of which the maximum permissible load is determined, and all the profiles of the typical sections are grouped together with the characteristics of the elements in a catalogue making it possible to select, as a function of the applied load, the passage cross-section to be obtained and the permitted clearance, the typical section profile which makes it possible to adhere as closely as possible to all requirements, the elements for the construction of the conduit being taken from stock or being produced in a desired number on the model of the elements constituting the typical section selected. <IMAGE> [origin: EP0381547A1] The subterranean duct construction system consists of excavating a trench or cutting and laying the duct or tunnel in the bottom of it in the form of prefabricated sections (101 104) for the floor and arched sections (201-206) for the roof. The prefabricated roof and floor sections can be made in a wider variety of shapes, according to the dimensions required for the finished duct or tunnel, and they can be made in one or two basic widths, so that a series of roof sections can be used with a series of base sections, giving a wide range of interchangeable sections.

IPC 1-7

E02B 9/06; F16L 1/038; E01F 5/00; E02D 29/045

IPC 8 full level

E01F 5/00 (2006.01); **E02D 29/045** (2006.01); **E02D 29/05** (2006.01); **F16L 1/038** (2006.01)

CPC (source: EP)

E01F 5/005 (2013.01); **E02D 29/045** (2013.01)

Cited by

EP1452646A3; CN109356045A; CN116240926A; EP0500444A1; FR2672937A1; FR2850984A1; FR2685304A1; EP1596010A1; FR2668183A1; FR2684401A1; CN101837789A; EP1452646A2; US11059201B2; WO9313344A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0381547 A1 19900808; EP 0381547 B1 19960717; AT E140502 T1 19960815; AT E178378 T1 19990415; CA 2008123 A1 19900720; CA 2008123 C 19930601; DE 69027791 D1 19960822; DE 69027791 T2 19970306; DE 69033036 D1 19990506; DK 0381547 T3 19961202; EP 0585959 A1 19940309; EP 0585959 B1 19990331; ES 2091809 T3 19961116; ES 2129477 T3 19990616; FR 2642110 A1 19900727; FR 2642110 B1 19910503; GR 3021286 T3 19970131

DOCDB simple family (application)

EP 90400144 A 19900118; AT 90400144 T 19900118; AT 93115365 T 19900118; CA 2008123 A 19900119; DE 69027791 T 19900118; DE 69033036 T 19900118; DK 90400144 T 19900118; EP 93115365 A 19900118; ES 90400144 T 19900118; ES 93115365 T 19900118; FR 8900700 A 19890120; GR 960402657 T 19961009