

Title (en)

SCAFFOLD WITH LATTICE GIRDER

Publication

**EP 0383317 B1 19930421 (DE)**

Application

**EP 90102921 A 19900215**

Priority

DE 3904638 A 19890216

Abstract (en)

[origin: EP0383317A1] The lattice girder (15) has a bottom flange (26), vertical bars (27), diagonal bars (28) and a top flange (25). A connection head (21) is fastened to each end (29.1 to 29.4) of top flange (25) and bottom flange (26). The top flange (25) is designed as an upwardly open U-section so as to be able to suspend directly the suspension means of scaffold platforms. A holding device with a pin for vertical scaffold poles can be additionally attached. <IMAGE>

IPC 1-7

**E04G 1/14**; **E04G 1/15**

IPC 8 full level

**E04G 1/14** (2006.01); **E04G 1/15** (2006.01)

CPC (source: EP)

**E04G 1/14** (2013.01); **E04G 1/15** (2013.01)

Cited by

CN114215323A; US11142925B2; AU775612B2; EP1016766A1; US2018251989A1; US10731362B2; EP3048214A1; CN107476568A; WO9823278A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0383317 A1 19900822**; **EP 0383317 B1 19930421**; AT E88533 T1 19930515; DE 3904638 A1 19900823; DE 59001219 D1 19930527; DK 0383317 T3 19930802; ES 2041060 T3 19931101; FI 900755 A0 19900215; NO 900715 D0 19900214; NO 900715 L 19900817; PT 9210 T 19960430; PT 9210 U 19970731; PT 93159 A 19900831

DOCDB simple family (application)

**EP 90102921 A 19900215**; AT 90102921 T 19900215; DE 3904638 A 19890216; DE 59001219 T 19900215; DK 90102921 T 19900215; ES 90102921 T 19900215; FI 900755 A 19900215; NO 900715 A 19900214; PT 921095 U 19951019; PT 9315990 A 19900215