

Title (en)

## FLOOR STRUCTURE FOR BUILDINGS

Publication

**EP 0385998 B1 19920610 (EN)**

Application

**EP 88906197 A 19880629**

Priority

SE 8702678 A 19870629

Abstract (en)

[origin: WO8900224A1] Floor structure for a building, for example, a parking garage, comprising primary beams (12), secondary beams (16-20) suspended on the primary beams and a lost form of sheet metal placed on the secondary beams. A concrete slab is poured in place in the form, which is trapezoidal and corrugated so that the concrete beams (47) are formed in the lower flanges of the form. The primary beams are lowered into the primary beams so that the concrete beams (47) are located below the level of the upper flanges (53) of the primary beams.

IPC 1-7

**E04B 5/40**

IPC 8 full level

**E04B 5/29** (2006.01); **E04B 5/40** (2006.01)

IPC 8 main group level

**E04B** (2006.01)

CPC (source: EP)

**E04B 5/29** (2013.01); **E04B 5/40** (2013.01)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

**WO 8900224 A1 19890112**; DE 3871960 D1 19920716; DE 3871960 T2 19930218; DK 164959 B 19920921; DK 164959 C 19930215;  
DK 660089 A 19891222; DK 660089 D0 19891222; EP 0385998 A1 19900912; EP 0385998 B1 19920610; FI 896312 A0 19891228;  
NO 895223 D0 19891222; NO 895223 L 19891222; SE 461108 B 19900108; SE 461109 B 19900108; SE 8702678 D0 19870629;  
SE 8702678 L 19881230; SE 8900176 D0 19890119; SE 8900176 L 19890119

DOCDB simple family (application)

**SE 8800358 W 19880629**; DE 3871960 T 19880629; DK 660089 A 19891222; EP 88906197 A 19880629; FI 896312 A 19891228;  
NO 895223 A 19891222; SE 8702678 A 19870629; SE 8900176 A 19890119