

Title (en)  
PLASTIC ELECTRODE

Publication  
**EP 0386077 B1 19910911 (DE)**

Application  
**EP 88909761 A 19881028**

Priority  
DE 3736576 A 19871028

Abstract (en)  
[origin: WO8903918A1] Known plastic electrodes, in particular those used in the drying of walls, have the drawback that they are practically ineffective after a very brief transition period. To obtain a conductive plastic electrode which has the same voltage potential over its entire surface, even when large, and which gives trouble-free performance for long periods, the electric line (3) having a lower resistance than that of the conductive plastics material of the plastic electrode (7) is conductively connected to the material of the plastic electrode (7) through a resistance connection (5). The resistance of the resistance connection is greater than that of the electric line (3) and that of the plastics material. The plastic electrode is particularly useful in the drying of walls.

IPC 1-7  
**E04B 1/70**

IPC 8 full level  
**E04B 1/70** (2006.01)

CPC (source: EP)  
**E04B 1/7007** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**WO 8903918 A1 19890505**; AT E67261 T1 19910915; DE 3736576 A1 19890511; DE 3736576 C2 19891116; DE 3864833 D1 19911017; EP 0386077 A1 19900912; EP 0386077 B1 19910911

DOCDB simple family (application)  
**EP 8800980 W 19881028**; AT 88909761 T 19881028; DE 3736576 A 19871028; DE 3864833 T 19881028; EP 88909761 A 19881028