

Title (en)

Trigger safety for a firearm.

Title (de)

Abzugsicherung an einer Schusswaffe.

Title (fr)

Dispositif de sûreté pour la détente d'une arme à feu.

Publication

EP 0386389 B1 19931201 (DE)

Application

EP 89810192 A 19890310

Priority

EP 89810192 A 19890310

Abstract (en)

[origin: EP0386389A1] A guide tube (7) is arranged on the buffer cylinder (6) at the rear end of an automatic firearm (1). A retaining ring (12) is slipped non-rotatably, but axially displaceably onto this guide tube (7). In a front operating position represented by unbroken lines, the retaining ring (12) prevents the trigger lever (2) from being pressed down and consequently any firing of a shot. In a rear operating position of the retaining ring (12), as represented by dot-and-dash lines, the trigger lever (2) can be freely actuated. The safety device is of simple construction and simple to operate and it can easily be attached to existing firearms. <IMAGE>

IPC 1-7

F41A 17/46; **F41A 19/33**

IPC 8 full level

F41A 17/46 (2006.01); **F41A 19/33** (2006.01)

CPC (source: EP US)

F41A 17/46 (2013.01 - EP US); **F41A 19/33** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0386389 A1 19900912; **EP 0386389 B1 19931201**; AT E98013 T1 19931215; DE 58906318 D1 19940113; ES 2047150 T3 19940216; US 5036749 A 19910806

DOCDB simple family (application)

EP 89810192 A 19890310; AT 89810192 T 19890310; DE 58906318 T 19890310; ES 89810192 T 19890310; US 48922590 A 19900306