

Title (en)
LOCKING CYLINDER KEY

Publication
EP 0386504 B1 19920129 (DE)

Application
EP 90103013 A 19900216

Priority
DE 3907065 A 19890304

Abstract (en)
[origin: EP0386504A1] Lock-cylinder keys can be provided with a key profile consisting of a plurality of profile parts (1, 2, 6) adjoining one another in a row and having individually distinguishable contours of capital letters. So that the profile variation of such keys can be recognised more easily, the profile parts (1, 2) having a contour (4, 5) of a capital letter or digit of at least double its written line width (s) are arranged above one another without any intermediate transition, whilst the profile part (1) forming the key spine has the contour of a letter (4) or digit (5) of a thickness at its outer end of a plurality of written line widths (s) and the profile part (2) forming the key breast has a contour of a letter (4) or digit (5) terminating at its outer end in a single written line width (s). <IMAGE>

IPC 1-7
E05B 19/00

IPC 8 full level
E05B 19/00 (2006.01); **E05B 19/06** (2006.01)

CPC (source: EP)
E05B 19/0029 (2013.01); **E05B 19/0041** (2013.01)

Cited by
NL1007788C2; IT202100030116A1; EP1600585A3; DE4305176A1; EP0611861A1; EP1437462A3; EP2290178A3; US11613909B1; US11536047B1; US11542724B1

Designated contracting state (EPC)
AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0386504 A1 19900912; EP 0386504 B1 19920129; AT E72289 T1 19920215; DE 3907065 A1 19900913; DE 3907065 C2 19920213; DE 59000037 D1 19920312; DE 8915622 U1 19901213; ES 2029140 T3 19920716

DOCDB simple family (application)
EP 90103013 A 19900216; AT 90103013 T 19900216; DE 3907065 A 19890304; DE 59000037 T 19900216; DE 8915622 U 19890304; ES 90103013 T 19900216