

Title (en)
LIGHTSTAND

Publication
EP 0386795 A3 19910911 (DE)

Application
EP 90104576 A 19900310

Priority
DE 3907805 A 19890310

Abstract (en)
[origin: EP0386795A2] A lightstand is proposed which comprises a hollow body (1), on the floor (2) and side faces (3) of which a reflecting layer is applied on the inside and in which a fluorescent tube is disposed as a light source (4) and the light exit aperture is provided with a diffusing surface (5). It is proposed that a partially transparent, partially reflective layer (6) be disposed in the light propagation direction in front of the diffusing surface (5), the transparency of which increases proportionally with the increase in the distance from the light source (4) to provide even illumination of the light exit aperture. <IMAGE>

IPC 1-7
G09F 13/04

IPC 8 full level
G09F 13/04 (2006.01); **G09F 13/14** (2006.01); **G09F 13/00** (2006.01)

CPC (source: EP)
G09F 13/0409 (2013.01); **G09F 13/14** (2013.01); **G09F 13/00** (2013.01); **G09F 2013/05** (2021.05)

Citation (search report)

- [Y] EP 0221018 A1 19870506 - HELD RETO
- [Y] EP 0225542 A1 19870616 - HINRICHS FOTOWERBUNG GMBH [DE]
- [A] AU 20642 B

Cited by
EP0446739A1; FR2678758A1; JPH04179990A; DE102010051307A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0386795 A2 19900912; EP 0386795 A3 19910911; EP 0386795 B1 19940706; AT E108280 T1 19940715; DE 3907805 A1 19900913; DE 59006331 D1 19940811

DOCDB simple family (application)
EP 90104576 A 19900310; AT 90104576 T 19900310; DE 3907805 A 19890310; DE 59006331 T 19900310