

Title (en)

FIRING MECHANISM FOR WEAPONS WITH AT LEAST TWO BARRELS, ESPECIALLY BREAK-DOWN GUNS

Publication

EP 0387704 B1 19911009 (DE)

Application

EP 90104436 A 19900308

Priority

DE 3908738 A 19890317

Abstract (en)

[origin: EP0387704A1] To provide for weapons with at least two barrels a single lock having only one striking piece (1) assigned to the striking pin (5 or 8) of one barrel or the other directly by means of the respective trigger (3 or 6), the striking piece (1) is connected rotatably to an articulated piece (2) in the manner of a toggle joint. In the folded position of the striking piece (1) and articulated piece (2), the striking piece (1) is aligned with the striking pin (5) of the lower barrel, whereas in the extended position of the striking piece (1) and articulated piece (2) the striking piece (1) is assigned to the striking pin (8) of the upper barrel. A catch device (1 a, 2a, 9, 10) is provided for the striking piece (1) and articulated piece (2). When one trigger (6) is actuated, this catch device releases the striking piece (1) and articulated piece (2) together in the extended position, so that the striking piece (1) butts against the striking pin (8) of the upper barrel. When the other trigger (3) is actuated, the catch device releases only the striking piece (1) in the folded position relative to the articulated piece (2) which remains locked. In this case, the striking piece (1) butts against the striking pin (5) of the lower barrel. <IMAGE>

IPC 1-7

F41A 19/18

IPC 8 full level

F41A 19/18 (2006.01); **F41A 19/22** (2006.01)

CPC (source: EP)

F41A 19/22 (2013.01)

Cited by

CN109930527A

Designated contracting state (EPC)

AT BE CH ES IT LI

DOCDB simple family (publication)

EP 0387704 A1 19900919; EP 0387704 B1 19911009; AT E68258 T1 19911015; DE 3908738 C1 19900412; ES 2027834 T3 19920616

DOCDB simple family (application)

EP 90104436 A 19900308; AT 90104436 T 19900308; DE 3908738 A 19890317; ES 90104436 T 19900308