

Title (en)  
Suspension insulator.

Title (de)  
Hängeisolator.

Title (fr)  
Isolateur de suspension.

Publication  
**EP 0388133 A2 19900919 (EN)**

Application  
**EP 90302638 A 19900313**

Priority  
JP 6686489 A 19890317

Abstract (en)  
Disclosed is a suspension insulator having a shed (2) with several ribs (4) formed concentrically and integrally on the lower face and a head (3) integrally formed at the central portion on the upper face of the shed(2), with a metal cap (5) being fixed on the head (3) and a metal pin (7) being fixed in the cavity of the head (3). The insulator is designed to have dimensions in such a way that the following equations [1] to [3] are satisfied:  $0.8 h < l$  [1]  $2.5 \leq L/H \leq 4.5$  [2]  $D \leq L$  [3], where, h is the height of the ribs (4); l is the interval between the ribs (4); L is the creepage distance as measured along the surface of the shed (2), D is the diameter of the shed (2); and H is the connection pitch of a suspension insulator unit forming an insulator string.

IPC 1-7  
**H01B 17/04; H01B 17/42**

IPC 8 full level  
**H01B 17/06** (2006.01); **H01B 17/04** (2006.01); **H01B 17/42** (2006.01); **H01B 17/50** (2006.01)

CPC (source: EP)  
**H01B 17/04** (2013.01); **H01B 17/42** (2013.01)

Cited by  
CN102208233A; CN103456428A; CN115143890A; WO2012131180A1

Designated contracting state (EPC)  
FR GB IT

DOCDB simple family (publication)  
**EP 0388133 A2 19900919; EP 0388133 A3 19910731; EP 0388133 B1 19951115**; EG 19239 A 19941030; JP H02244514 A 19900928; JP H077612 B2 19950130

DOCDB simple family (application)  
**EP 90302638 A 19900313**; EG 16990 A 19900314; JP 6686489 A 19890317