

Title (en)
FIRE PROTECTION DOOR

Publication
EP 0388774 B1 19930922 (DE)

Application
EP 90104789 A 19900314

Priority
DE 3909638 A 19890323

Abstract (en)
[origin: EP0388774A2] The fire-proof door is formed from a box-shaped door leaf (1) which encloses mineral-fibre panels (5). The visible sides of the door leaf (1) consist of two cover plates (2, 3), and the end faces are formed with a frame (4). A gap between edges (6) of angled edge strips (7) of the cover plates (2, 3) is bridged by the frame (4). Longitudinal edge strips (14) of the frame (4), which are angled in the interior of the door leaf (1), engage in grooves (15) provided in end faces of the mineral-fibre panels (5). The profile of the frame (4) is provided in its central region with a groove (8) which is open to the outside and in which are provided a strip (10) which foams under the action of heat, and a plaster channel (11). The frame (4) holds the mineral-fibre panels (5) at a parallel spacing, so that these parts form a compact, pre-manufacturable construction unit to which the cover plates (2, 3) can be positively attached at both sides. <IMAGE>

IPC 1-7
E06B 5/16

IPC 8 full level
E06B 5/16 (2006.01)

CPC (source: EP)
E06B 5/164 (2013.01)

Cited by
NL1016562C2

Designated contracting state (EPC)
AT BE CH DE ES FR GR IT LI NL SE

DOCDB simple family (publication)
EP 0388774 A2 19900926; EP 0388774 A3 19901219; EP 0388774 B1 19930922; AT E82036 T1 19921115; AT E94945 T1 19931015; DE 59000421 D1 19921210; DE 59002787 D1 19931028; EP 0388773 A2 19900926; EP 0388773 A3 19901219; EP 0388773 B1 19921104; ES 2035669 T3 19930416; PT 93543 A 19911031; PT 93543 B 19960531; PT 93544 A 19911031

DOCDB simple family (application)
EP 90104789 A 19900314; AT 90104788 T 19900314; AT 90104789 T 19900314; DE 59000421 T 19900314; DE 59002787 T 19900314; EP 90104788 A 19900314; ES 90104788 T 19900314; PT 9354390 A 19900322; PT 9354490 A 19900322