

Title (en)
METHOD AND APPARATUS FOR TREATING A LIQUID MIXTURE

Publication
EP 0389405 B1 19930210 (EN)

Application
EP 90630064 A 19900315

Priority
IL 8968589 A 19890320

Abstract (en)
[origin: EP0389405A2] Treating a liquid mixture to separate a clarified fraction therefrom leaving a concentrated sludge fraction involves injecting a flocculent material into the liquid mixture; and inletting the liquid material and the flocculent material tangentially into a vertical tank (12) having a perforated plate (20) spaced from its upper end dividing the tank (12) into an upper chamber (12a) and a lower chamber (12b), to produce a flow in the lower chamber (12b) having a rotational velocity in the horizontal direction adjacent the outer periphery of the lower chamber (12b), and a lower rotational velocity in the horizontal direction adjacent the center of the lower chamber (12b). The holes (20a) in the perforated plate (20) define reduced-area passages from the lower chamber (12b) to the upper chamber (12a) producing a vertical flow of low velocity in the lower chamber (12b) and of higher velocity through the passages (20a) in the perforated plate (20).

IPC 1-7
C02F 1/52

IPC 8 full level
C02F 1/52 (2006.01)

CPC (source: EP US)
C02F 1/5281 (2013.01 - EP US)

Cited by
EP2017231A1; AT408630B; EP1004339A1; US5350511A; EP0514543A4

Designated contracting state (EPC)
ES FR GB GR IT NL

DOCDB simple family (publication)
EP 0389405 A2 19900926; EP 0389405 A3 19910116; EP 0389405 B1 19930210; ES 2038508 T3 19930716; GR 3007261 T3 19930730; IL 89685 A0 19890928; IL 89685 A 19930404; US 5082560 A 19920121; ZA 901913 B 19910327

DOCDB simple family (application)
EP 90630064 A 19900315; ES 90630064 T 19900315; GR 930400481 T 19930309; IL 8968589 A 19890320; US 45754790 A 19900309; ZA 901913 A 19900313