

Title (en)  
FLAT-CONTACT RECEPTACLE.

Title (de)  
FLACHKONTAKTSTECKHÜLSE.

Title (fr)  
CONTACT A LANGUETTES.

Publication  
**EP 0389575 B1 19951108 (DE)**

Application  
**EP 89907734 A 19890713**

Priority  
• DE 3826670 A 19880805  
• EP 8900813 W 19890713

Abstract (en)  
[origin: WO9001815A1] A flat-pin receptacle comprises two contact tabs arranged on the receptacle body and resiliently in contact with each other along part of their length. A connecting spring surrounding the receptacle body presses against the outsides of each contact tab along two strip-shaped sections on the connecting spring body arranged at a distance apart. The receptacle body has recesses for receiving locking tongues which are arranged on, and can be bent away from, the receptacle housing. To facilitate assembly of the locking tongues in receptacle housings, a strip part (14) is arranged on both sides of the connecting spring (12') between the sections (13) and parallel to the latter. The strip parts (14) are bent back towards each other and inward over the free ends of the contact tabs (6) along part of their length opposite the connecting spring body (12').

IPC 1-7  
**H01R 13/18**

IPC 8 full level  
**H01R 13/15** (2006.01); **H01R 13/18** (2006.01); **H01R 13/422** (2006.01)

CPC (source: EP US)  
**H01R 13/4223** (2013.01 - EP US); **H01R 13/18** (2013.01 - EP US)

Designated contracting state (EPC)  
AT BE DE FR GB IT NL SE

DOCDB simple family (publication)  
**WO 9001815 A1 19900222**; AT E130127 T1 19951115; BR 8907048 A 19910102; DE 3826670 A1 19900208; DE 3826670 C2 19941117; DE 58909488 D1 19951214; EP 0389575 A1 19901003; EP 0389575 B1 19951108; JP 2929496 B2 19990803; JP H03501425 A 19910328; US 5035661 A 19910730

DOCDB simple family (application)  
**EP 8900813 W 19890713**; AT 89907734 T 19890713; BR 8907048 A 19890713; DE 3826670 A 19880805; DE 58909488 T 19890713; EP 89907734 A 19890713; JP 50748389 A 19890713; US 46958590 A 19900425