

Title (en)
Electrical connector assembly.

Title (de)
Elektrische Kupplungsvorrichtung.

Title (fr)
Dispositif de connexion électrique.

Publication
EP 0390006 A1 19901003 (DE)

Application
EP 90105668 A 19900326

Priority
DE 3910117 A 19890329

Abstract (en)
In an electrical connector assembly, a slide is used which moves at right angles to the plug-in direction of the first and of the second housing, in order to be able to couple or decouple the associated contact and mating contact elements held in the housings easily. In order in this case to avoid sealing problems in guiding the slide it is proposed that the first housing be split into two plug parts, connected to one another, and that the second housing be split into two socket parts, which are complementary thereto, which socket parts are in each case located at a distance from one another at right angles to the plug-in direction of the housing parts and on which the contact and mating contact elements are distributed. A single-wall control printed-circuit board is used as the slide, which is located outside the housing, namely in a plane between the plug parts and the socket parts. Each plug part with its socket part is inherently sealed, without it being adversely affected by the control printed-circuit board. <IMAGE>

Abstract (de)
Bei einer elektrischen Kupplungsvorrichtung verwendet man einen quer zur Steckrichtung des ersten und zweiten Gehäuses beweglichen Schieber, um die zugehörigen, in den Gehäusen gehaltenen Kontakt- und Gegen-Kontaktglieder leicht kuppeln oder entkuppeln zu können. Um dabei Dichtungsprobleme bei der Führung des Schiebers zu vermeiden, wird vorgeschlagen, das erste Gehäuse in zwei miteinander verbundene Steckteile und das zweite Gehäuse in zwei dazu komplementäre Aufnahme-Teile zu gliedern, welche jeweils quer zur Steckrichtung der Gehäuseteile in Abstand zueinander liegen und auf welche sich die Kontakt- und Gegen-Kontaktglieder verteilen. Als Schieber wird eine einwandige Steuerplatte verwendet, die außerhalb des Gehäuses liegt, und zwar in einer Ebene zwischen den Steckteilen und den Aufnahmeteilen. Jedes Steckteil ist mit seinem Aufnahmeteil für sich abgedichtet, ohne daß dies durch die Steuerplatte beeinträchtigt wird.

IPC 1-7
H01R 13/629; **H01R 13/639**; **H01R 23/02**

IPC 8 full level
H01R 13/629 (2006.01); **H01R 13/639** (2006.01); **H01R 13/436** (2006.01); **H01R 13/52** (2006.01)

CPC (source: EP)
H01R 13/62916 (2013.01); **H01R 13/4362** (2013.01); **H01R 13/521** (2013.01)

Citation (search report)
• [A] US 4344663 A 19820817 - OGNIER PAUL, et al
• [A] US 4377319 A 19830322 - MACDOUGALL ALAN R
• [A] DE 3818092 A1 19881222 - YAZAKI CORP [JP]
• [A] DE 1590015 B2 19711230
• [A] DE 2942569 A1 19800430 - GEN MOTORS CORP

Cited by
EP0867975A3; DE19530335A1; DE19530335B4; EP3706250A1; FR3093596A1; US11205868B2

Designated contracting state (EPC)
AT BE DE ES FR GB IT SE

DOCDB simple family (publication)
EP 0390006 A1 19901003; **EP 0390006 B1 19940420**; AT E104803 T1 19940515; DE 3910117 C1 19900913; DE 59005402 D1 19940526; ES 2056277 T3 19941001

DOCDB simple family (application)
EP 90105668 A 19900326; AT 90105668 T 19900326; DE 3910117 A 19890329; DE 59005402 T 19900326; ES 90105668 T 19900326