

Title (en)

ELECTRODE CONSTRUCTION OF BATTERY IN ELECTRICAL EQUIPMENT

Publication

EP 0390070 A3 19910904 (EN)

Application

EP 90105810 A 19900327

Priority

JP 7765189 A 19890328

Abstract (en)

[origin: EP0390070A2] The present invention is directed to an electrode construction of a battery (1) in an electrical equipment. According to the present invention, at least two contacts (8a, 8b; 5a, 5b) in an electrode (4, 7) have a different shape from each other, so that the characteristic frequencies of these contacts are different from each other. As a result, when a contact is resonating by the frequency of an oscillation applied to the electrical equipment, the other contact keeps in contact with the battery (1) without resonating.

IPC 1-7

H01R 13/24; H01R 13/11

IPC 8 full level

B42D 25/305 (2014.01); **G06F 1/26** (2006.01); **G06K 19/00** (2006.01); **G06K 19/077** (2006.01); **H01M 2/10** (2006.01); **H01R 13/24** (2006.01)

CPC (source: EP)

H01R 13/2492 (2013.01)

Citation (search report)

- [A] US 4718742 A 19880112 - UTOH YOSHIHIRO [JP], et al
- [A] DE 2706760 B2 19800717
- [A] DE 2823285 A1 19791129 - PREH ELEKTRO FEINMECHANIK
- [A] US 4371595 A 19830201 - SUWA KANAME [JP]

Cited by

EP1973202A1; US9033750B2; WO2014028266A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0390070 A2 19901003; EP 0390070 A3 19910904; EP 0390070 B1 19941130; DE 69014370 D1 19950112; DE 69014370 T2 19950713;
JP H02253999 A 19901012; JP H074996 B2 19950125

DOCDB simple family (application)

EP 90105810 A 19900327; DE 69014370 T 19900327; JP 7765189 A 19890328