

Title (en)
MEANS FOR HOLDING A PIVOTING PANEL

Publication
EP 0391238 B1 19930113 (DE)

Application
EP 90105951 A 19900328

Priority
DE 3911319 A 19890407

Abstract (en)
[origin: EP0391238A2] So that a pivoting part (12), for example the window or roof light of a vehicle, can be swung out and retained in a specific position, there is arranged between the pivoting part (12) and a receiving part (16) at least one guide rail (22) with an approximately longitudinally extending groove (52) having at least one indentation (54). The guide rail (22) is pivotably mounted at one end on one of the parts (12, 16). It receives slidably in its groove (52) a pin (48) connected to the other part (12, 16). Furthermore, a block (24) displaceable along the guide rail (22) is provided. This is so designed that, as a rule, it covers the indentation (54) of the guide rail (22) and exposes it only in a retention position. In the retention position, the pin (48) can engage into the indentation (54) of the guide rail (22) and be supported on a side face (58) of the indentation (54). During the opening or closing of the pivoting part (12), the block (24) is displaced on the guide rail (22) as a result of the engagement of the pin (48). Arranged between the pivoting part (12) and receiving part (16) in parallel with the retaining device (18) is a pneumatic spring (20) which endeavours to bring the pivoting part (12) into an opened position. <IMAGE>

IPC 1-7
E05C 17/16

IPC 8 full level
E05F 3/22 (2006.01); **E05C 17/08** (2006.01); **E05C 17/16** (2006.01)

CPC (source: EP US)
E05C 17/085 (2013.01 - EP US); **E05C 17/16** (2013.01 - EP US); **Y10S 292/04** (2013.01 - EP US); **Y10T 292/289** (2015.04 - EP US)

Citation (examination)
• DE 1037918 B 19580828 - JEAN MAWHIN SA
• DE 2217797 A1 19731025 - GIEHL & CO

Cited by
EP0507708A1; FR2674879A1; EP0978615A3; DE102015108200A1

Designated contracting state (EPC)
AT DE DK ES FR GB IT SE

DOCDB simple family (publication)
EP 0391238 A2 19901010; EP 0391238 A3 19910807; EP 0391238 B1 19930113; AT E84595 T1 19930115; DE 3911319 A1 19901011; DE 3911319 C2 19910516; DE 59000733 D1 19930225; DK 0391238 T3 19930208; ES 2037493 T3 19930616; FI 901708 A0 19900404; FI 90581 B 19931115; FI 90581 C 19940225; JP H02296983 A 19901207; US 5071180 A 19911210

DOCDB simple family (application)
EP 90105951 A 19900328; AT 90105951 T 19900328; DE 3911319 A 19890407; DE 59000733 T 19900328; DK 90105951 T 19900328; ES 90105951 T 19900328; FI 901708 A 19900404; JP 9297890 A 19900407; US 50065490 A 19900327