

Title (en)

Aluminium-based alloy with a high modulus and an increased mechanical strenght and process for production.

Title (de)

Legierung auf Aluminiumbasis mit einem hohen Modul und mit einer erhöhten mechanischen Festigkeit und Verfahren zur Herstellung.

Title (fr)

Alliage à base d'A1 à haut module et à resistance mécanique élevée et procédé d'obtention.

Publication

EP 0391815 A1 19901010 (FR)

Application

EP 90420166 A 19900403

Priority

FR 8904700 A 19890405

Abstract (en)

Al-based alloys of the 7000 series which have a high modulus ($E \geq 74$ GPa), a high mechanical strength ($R_{0.2} \geq 530$ MPa in the lengthwise direction), a good tenacity (KIC, lengthwise direction > 20 MPa $\sqrt{\text{m}}$) and a good corrosion resistance under (O pressure ≥ 250 MPa in the short transverse direction, lifetime ≥ 30 days - ASTM Standard G 38-73). <??>The alloy according to the invention corresponds to the following weight composition: from 5.5 to 8.45% of Zr from 2 to 3.5% Mg from 0.5 to 2.5% Cu up to 0.5% Fe up to 0.5% Si other elements $\leq 0.05\%$ each and up to 0.15% in all with $0.1 \leq \text{Zr} \leq 0.5\%$ $0.3 \leq \text{Cr} \leq 0.6\%$ $0.3 \leq \text{Mn} \leq 1.1\%$ <??>It is preferably produced by the following process: a) a massive body which has the composition claimed above is formed by spray-deposition, b) this body is converted into a wrought product between 300 and 450 DEG C and then optionally when cold c) the wrought product is heat-treated by dissolving, quenching and annealing to a T6 or T7 state. <IMAGE>

IPC 1-7

C22C 1/04; **C22C 21/10**; **C22C 32/00**; **C22F 1/053**

IPC 8 full level

C22C 1/04 (2006.01); **C22C 21/10** (2006.01); **C22F 1/00** (2006.01); **C22F 1/053** (2006.01)

CPC (source: EP US)

C22C 1/0416 (2013.01 - EP US); **C22C 21/10** (2013.01 - EP US); **C22F 1/053** (2013.01 - EP US); **Y10S 428/937** (2013.01 - EP US); **Y10T 428/12486** (2015.01 - EP US); **Y10T 428/12799** (2015.01 - EP US)

Citation (search report)

- [X] EP 0105595 A2 19840418 - ALCAN INT LTD [CA]
- [X] US 3791876 A 19740212 - KROGER P
- [X] FR 1322510 A 19630329 - ALUMINUM CO OF AMERICA
- [Y] EP 0081441 A1 19830615 - GERZAT METALLURG [FR]
- [Y] EP 0198606 A1 19861022 - ATOMIC ENERGY AUTHORITY UK [GB]
- [A] US 3563814 A 19710216 - LYLE JOHN P JR, et al
- [A] POWDER METALLURGY, vol. 28, no. 2, 1985, pages 72-78, Londres, GB; A.R.E. SINGER et al.: "Metal matrix composites produced by spray codeposition"
- [A] W. HUFNAGEL: "Aluminium-Taschenbuch", édition 14, 1983, pages 1011-1018, Aluminium-Verlag, Düsseldorf, DE

Cited by

EP1241275A4; CN103255327A; RU2676817C2; US6726878B1; US10301710B2

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0391815 A1 19901010; **EP 0391815 B1 19950125**; AT E117734 T1 19950215; BR 9001576 A 19910430; CA 2013270 A1 19901005; DD 293144 A5 19910822; DE 69016241 D1 19950309; DE 69016241 T2 19950524; FR 2645546 A1 19901012; FR 2645546 B1 19940325; HU 901848 D0 19900828; HU T57281 A 19911128; IL 93904 A0 19901223; JP H032345 A 19910108; NO 901415 D0 19900328; NO 901415 L 19901008; US 5047092 A 19910910; US 5110372 A 19920505

DOCDB simple family (application)

EP 90420166 A 19900403; AT 90420166 T 19900403; BR 9001576 A 19900404; CA 2013270 A 19900329; DD 33915290 A 19900328; DE 69016241 T 19900403; FR 8904700 A 19890405; HU 184890 A 19900327; IL 9390490 A 19900327; JP 9003590 A 19900404; NO 901415 A 19900328; US 50390390 A 19900404; US 67492291 A 19910326