

Title (en)  
PNEUMATIC HAMMER

Publication  
**EP 0391856 A3 19920708 (DE)**

Application  
**EP 90810267 A 19900403**

Priority  
CH 132089 A 19890407

Abstract (en)  
[origin: EP0391856A2] The hammer has two handles (11, 12) projecting transversely from the housing (1). Said handles are attached to the free ends of a leaf spring (10) bent in a Z-shape. The bends (13, 14) of the spring (10) wind round rollers (15, 16), fixed to the housing, with play. A pusher (22) is pivotably mounted on one handle (11). It has a connecting link (27), the centre of curvature of which coincides approximately with the centre of pivoting (26) of the associated handle (11) when the pusher (22) is actuated. The connecting link (27) actuates, via transmission members (31, 32), a valve pin (5) of the hammer. As a result of this design, the handles (11, 12) can be effectively protected not only from the base frequencies, but also higher-frequency vibrations of the hammer. Even when pulling the hammer, this design is at least partly effective. <IMAGE>

IPC 1-7  
**B25D 17/04**

IPC 8 full level  
**B25D 17/04** (2006.01)

CPC (source: EP)  
**B25D 17/043** (2013.01); **B25D 2250/381** (2013.01)

Citation (search report)  
• [X] US 3372759 A 19680312 - PHILIPP UEBEL  
• [X] GB 2138348 A 19841024 - ANDERSSON ROLAND  
• [A] FR 2540774 A1 19840817 - MACO MEUDON SA [FR]  
• [A] GB 242218 A 19260311 - INGERSOLL RAND CO  
• [XP] EP 0343656 A2 19891129 - KYOWA METAL WORKS CO LTD [JP]

Cited by  
EP0537875A1; FR2808719A1; EP1166972A3; US2022314412A1; US12048993B2; WO2013030380A1; WO0187546A1; WO9427789A1

Designated contracting state (EPC)  
AT CH DE FR GB IT LI SE

DOCDB simple family (publication)  
**EP 0391856 A2 19901010; EP 0391856 A3 19920708; AU 5307190 A 19901011**

DOCDB simple family (application)  
**EP 90810267 A 19900403; AU 5307190 A 19900406**