

Title (en)

Axle with primary suspension and variable orientation.

Title (de)

Achse mit Primäraufhängung und veränderlicher Orientierung.

Title (fr)

Essieu à suspension primaire et à orientation variable.

Publication

EP 0392414 B1 19940302 (FR)

Application

EP 90106743 A 19900409

Priority

FR 8904680 A 19890410

Abstract (en)

[origin: EP0392414A2] Railway vehicle axle with primary suspension and variable orientation, rotating between two axle boxes and mounted on a frame, possessing a primary suspension comprising, for each of the axle boxes, two resilient blocks arranged on either side of the axle box, characterised in that the said blocks (5A, 5B) have an internal cavity connected, via a distribution system, to a source of fluid of adjustable pressure.
<IMAGE>

IPC 1-7

B61F 5/38

IPC 8 full level

B61F 5/30 (2006.01); **B61F 5/38** (2006.01); **B61F 5/44** (2006.01)

CPC (source: EP)

B61F 5/386 (2013.01)

Cited by

GB2579344A; GB2579344B; US5199359A; EP3241716A1; AT518699A1; WO2016131688A1; WO2018095961A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0392414 A2 19901017; EP 0392414 A3 19901205; EP 0392414 B1 19940302; AT E102135 T1 19940315; CA 2014168 A1 19901010; CA 2014168 C 19940719; DE 69006886 D1 19940407; DE 69006886 T2 19940609; DK 0392414 T3 19940524; ES 2050865 T3 19940601; FR 2645483 A1 19901012; FR 2645483 B1 19930430; JP H02293252 A 19901204; JP H072463 B2 19950118

DOCDB simple family (application)

EP 90106743 A 19900409; AT 90106743 T 19900409; CA 2014168 A 19900409; DE 69006886 T 19900409; DK 90106743 T 19900409; ES 90106743 T 19900409; FR 8904680 A 19890410; JP 9491490 A 19900410