

Title (en)

METHOD AND DEVICE FOR SUPPLYING DAMPING LIQUID IN AN OFFSET PRINTING MACHINE

Publication

EP 0393365 A3 19910522 (DE)

Application

EP 90105186 A 19900320

Priority

DE 3912811 A 19890419

Abstract (en)

[origin: CA2014950A1] The invention relates to a method for determining the delivery of a moistening agent to an offset printing machine. For subject-dependent moistening-agent adjustment, it is proposed that inking of the printing plate (6) be carried out with acquisition of ink (toning) from ink-free areas in the production-run process, and that a specific delivery of moistening agent, or an increase in the delivery of moistening agent, shall then take place, including the ink-reducing process of the toning areas, which is used as a criterion for the moistening-agent delivery to be adjusted. In addition to this, a device for moistening-agent delivery is provided.

IPC 1-7

B41F 33/00; **B41F 7/24**

IPC 8 full level

B41F 7/24 (2006.01); **B41F 33/00** (2006.01); **B41F 33/10** (2006.01)

CPC (source: EP US)

B41F 7/24 (2013.01 - EP US); **B41F 33/0027** (2013.01 - EP US); **B41F 33/0054** (2013.01 - EP US); **Y10S 101/45** (2013.01 - EP US)

Citation (search report)

[X] CA 863048 A 19710209 - KANTOR PAUL R

Cited by

EP0700782A3; EP1261486A4; US5568769A; US8534194B2; WO9411192A1; WO2008049500A3; EP1477314B1

Designated contracting state (EPC)

DE ES FR GB IT NL

DOCDB simple family (publication)

EP 0393365 A2 19901024; **EP 0393365 A3 19910522**; **EP 0393365 B1 19940831**; CA 2014950 A1 19901019; DE 3912811 A1 19901025; DE 59006941 D1 19941006; JP H02295741 A 19901206; US 5090316 A 19920225

DOCDB simple family (application)

EP 90105186 A 19900320; CA 2014950 A 19900419; DE 3912811 A 19890419; DE 59006941 T 19900320; JP 10185590 A 19900419; US 51105790 A 19900419