

Title (en)

PRINT GAP ADJUSTMENT MECHANISM IN A PRINTER

Publication

EP 0393759 A3 19910724 (DE)

Application

EP 90200897 A 19900412

Priority

DE 3913073 A 19890421

Abstract (en)

[origin: EP0393759A2] For the simple and precise adjustment of a print gap in a printer, e.g. a matrix needle printer, it is proposed a) that the print head is moved several times back and forth between two switch points and is moved at the same time forwards in the direction of the print abutment, b) that the contact between the print abutment and the print head is determined by changing a parameter characterising the back and forth movement, c) that this change leads to the stoppage of the forward movement when a certain value is reached, and d) that, starting from this position with the print gap "zero", the print head is moved back by the desired value of the print gap. <IMAGE>

IPC 1-7

B41J 25/308

IPC 8 full level

B41J 25/308 (2006.01)

CPC (source: EP US)

B41J 25/308 (2013.01 - EP US); **B41J 25/3088** (2013.01 - EP US)

Citation (search report)

- [A] US 4676675 A 19870630 - SUZUKI YOSHIHUMI [JP], et al
- [A] EP 0292102 A1 19881123 - FUJITSU LTD [JP]
- [A] US 4652153 A 19870324 - KOTSUZUMI YUZO [JP], et al

Cited by

EP0510768A3; DE19703883A1; EP0657294A3; DE19813899A1; EP0947343A3

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

EP 0393759 A2 19901024; EP 0393759 A3 19910724; EP 0393759 B1 19940706; DE 3913073 A1 19901025; DE 59006336 D1 19940811; JP H02295781 A 19901206; US 5009526 A 19910423

DOCDB simple family (application)

EP 90200897 A 19900412; DE 3913073 A 19890421; DE 59006336 T 19900412; JP 10052190 A 19900418; US 50803490 A 19900410