

Title (en)

APPARATUS FOR THE CONTINUOUS PRODUCTION OF A MULTIVALENT METAL BY ELECTROLYSIS OF A HALIDE THEREOF DISSOLVED IN A MOLTEN BATH

Publication

EP 0394154 B1 19930616 (FR)

Application

EP 90420196 A 19900419

Priority

FR 8906134 A 19890421

Abstract (en)

[origin: EP0394154A1] Apparatus for continuous production of a polyvalent metal by electrolysis of a halide in a bath (2) of at least one molten salt. <??>It consists - of an electrodisproportionation cell (a) in the bath of which there are immersed at least one deposition cathode (4) and at least two anodes (5) connected to a source of at least partially direct electrical current; - of a prerduction cell (b) in the bath of which there are immersed at least one anode (6) and a cathode (3) which are separated from each other by a diaphragm (7) and are connected to a source of at least partially direct electrical current; - the cells (a) and (b) being adjoining and their common wall consisting of a grid insulated electrically from the walls of the cell and negatively polarised and forming the cathode (3) through which the bath travels by means of forced convection. <??>This apparatus makes it possible to dispense with variations in the composition and valency of the bath in the metal deposition zone and to prevent the formation of halogen near this zone. <IMAGE>

IPC 1-7

C25C 3/00; **C25C 3/26**

IPC 8 full level

C25C 3/00 (2006.01); **C25C 3/26** (2006.01); **C25C 3/34** (2006.01); **C25C 7/00** (2006.01)

CPC (source: EP US)

C25C 3/00 (2013.01 - EP US); **C25C 3/26** (2013.01 - EP US)

Designated contracting state (EPC)

AT CH DE FR GB IT LI SE

DOCDB simple family (publication)

EP 0394154 A1 19901024; **EP 0394154 B1 19930616**; AT E90741 T1 19930715; DE 69001949 D1 19930722; DE 69001949 T2 19931007; JP H0394088 A 19910418; JP H0823077 B2 19960306; NO 179014 B 19960409; NO 179014 C 19960717; NO 901757 D0 19900420; NO 901757 L 19901022; US 5013413 A 19910507

DOCDB simple family (application)

EP 90420196 A 19900419; AT 90420196 T 19900419; DE 69001949 T 19900419; JP 10512290 A 19900420; NO 901757 A 19900420; US 50913190 A 19900416