

Title (en)

METHOD AND DEVICE FOR SENSING THE DIRECTION OF CRANKSHAFT ROTATION IN A DIESEL ENGINE

Publication

EP 0394290 B1 19920304 (EN)

Application

EP 88909094 A 19880927

Priority

EP 8800868 W 19880927

Abstract (en)

[origin: WO9003508A1] A method and device for sensing the direction of crankshaft rotation in a diesel engine relies on measuring the angular difference (alpha) between a reference mark (BM) dependent on crankshaft rotation and commencement of fuel injection (FB). Since the normally trailing flank of the cam of the fuel injection pump, effectively becomes the leading flank on reverse rotation, this angular difference becomes substantially larger or substantially smaller than a reference (alpha r) in the event of the reverse rotation. The signal produced upon reverse rotation can be used to stop the engine immediately.

IPC 1-7

F02D 41/22

IPC 8 full level

F02D 41/22 (2006.01); **F02D 41/38** (2006.01); **F02D 45/00** (2006.01); **F02B 3/06** (2006.01)

CPC (source: EP KR)

F02D 41/22 (2013.01 - EP KR); **F02D 41/38** (2013.01 - EP); **F02B 3/06** (2013.01 - EP); **F02D 2041/226** (2013.01 - EP);
F02D 2250/06 (2013.01 - EP)

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

WO 9003508 A1 19900405; DE 3868944 D1 19920409; EP 0394290 A1 19901031; EP 0394290 B1 19920304; JP H03501511 A 19910404;
KR 0121319 B1 19971124; KR 900702205 A 19901206

DOCDB simple family (application)

EP 8800868 W 19880927; DE 3868944 T 19880927; EP 88909094 A 19880927; JP 50839788 A 19880927; KR 900701087 A 19900525