

Title (en)

APPARATUS TO AVOID GOING UNDER THE DEW POINT NEAR WINDOW FLASHINGS

Publication

EP 0395777 B1 19920909 (DE)

Application

EP 89107972 A 19890503

Priority

EP 89107972 A 19890503

Abstract (en)

[origin: EP0395777A1] In known constructions and, in particular, in the renovation of old buildings, the problem arises that in the region of the flashings of windows and doors, the dew-point isotherm is not located in the window frame (7) but appears at the materials in the region of the interior, thereby resulting in a discontinuity in the curve of the dew-point isotherm. In order to avoid this disadvantage, the invention proposes that the curve of the dew-point isotherm of the room climate running through the heat-insulating zone (2) in the region of the static layer zone (1) or the monolithic wall passes without discontinuity or interruption into the window frame (7). <IMAGE>

IPC 1-7

E06B 1/62

IPC 8 full level

E06B 1/00 (2006.01); **E06B 1/62** (2006.01)

CPC (source: EP)

E06B 1/00 (2013.01); **E06B 1/62** (2013.01)

Citation (examination)

- E. NEUFERT: "BAUENTWURFSLEHRE", 30. Auflage, 1979, Seiten 102, 103, Friedrich Vieweg & Sohn, Braunschweig/Wiesbaden, DE: "Wärmebrücken"
- BBZ - DEUTSCHE BAUZEITSCHRIFT Nr. 9, September 1988, Seiten 1199-1204, Gütersloh, DE; J. SCHMID: "Fensteranschlüsse am Baukörper"

Cited by

EP0796972A3; WO2008120262A3

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0395777 A1 19901107; **EP 0395777 B1 19920909**; AT E80439 T1 19920915; DE 58902257 D1 19921015; ES 2034473 T3 19930401

DOCDB simple family (application)

EP 89107972 A 19890503; AT 89107972 T 19890503; DE 58902257 T 19890503; ES 89107972 T 19890503