

Title (en)
Output apparatus.

Title (de)
Ausgabegerät.

Title (fr)
Appareil de sortie.

Publication
EP 0398681 A2 19901122 (EN)

Application
EP 90305278 A 19900516

Priority
JP 12145489 A 19890517

Abstract (en)
There is provided an output apparatus for receiving code data from a data source of a host computer and developing into pattern data and outputting. The apparatus comprises: a pattern generator to generate pattern data; a memory to store the pattern data generated from the pattern generator as a font cache; and a controller for controlling in a manner such that when a residual amount of the memory is less than a capacity enough to store other data which is newly input and whose priority regarding the storage is higher than the priority of the pattern data, the pattern data of the font cache is deleted and the newly input data is stored. An auxiliary character font, form data, or a macro instruction is used as data which is newly input. The pattern data of the font cache in the memory is deleted on the basis of the priority. The pattern data is a dot matrix font pattern which was developed from a nondot matrix font.

IPC 1-7
G06K 15/02; **G06K 15/10**

IPC 8 full level
B41J 2/485 (2006.01); **B41J 5/44** (2006.01); **G06F 3/12** (2006.01); **G06K 15/02** (2006.01); **G09G 5/22** (2006.01)

CPC (source: EP US)
G06K 15/02 (2013.01 - EP US); **G06K 2215/0005** (2013.01 - EP US); **G06K 2215/0042** (2013.01 - EP US)

Cited by
EP0554998A1; EP0849701A3; US5587800A; EP0661669A3; US5734748A; US6611347B1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0398681 A2 19901122; **EP 0398681 A3 19911204**; **EP 0398681 B1 19961106**; DE 69029054 D1 19961212; DE 69029054 T2 19970313; JP 2610993 B2 19970514; JP H02301464 A 19901213; US 5522028 A 19960528

DOCDB simple family (application)
EP 90305278 A 19900516; DE 69029054 T 19900516; JP 12145489 A 19890517; US 24742094 A 19940523