

Title (en)

STRIP FOR MAKING A CONSTRUCTION WATERTIGHT

Publication

EP 0399952 B1 19930428 (DE)

Application

EP 90810361 A 19900516

Priority

CH 196089 A 19890525

Abstract (en)

[origin: EP0399952A1] For sealing or covering openings in a construction, a permanently elastic strip consisting of a base layer (1) and a foamed-material layer (2) of open-cell foam structure is used. The foamed-material layer (2) is, on the one hand, watertight and allows, on the other hand, water vapour to pass through. The foamed-material layer is preferably composed of PVC and has a diffusion resistance value (SD) equal to or less than 1.3 m. <IMAGE>

IPC 1-7

E04B 1/68

IPC 8 full level

E04B 1/68 (2006.01); **E04B 1/684** (2006.01)

CPC (source: EP)

E04B 1/6809 (2013.01)

Cited by

EP1473419A3; EA010560B1; EP1473418A3; EP1088944A3; CN110130508A; EP3584380A1; GB2444121A; AT518547A4; AT518547B1; US5733824A; US5869408A; US5881521A; US5895301A; US5593771A; WO9418407A1; WO2006061088A1; EP0837768B1

Designated contracting state (EPC)

AT BE CH DE FR IT LI LU NL

DOCDB simple family (publication)

EP 0399952 A1 19901128; EP 0399952 B1 19930428; AT E88778 T1 19930515; CH 678871 A5 19911115; DE 59001290 D1 19930603

DOCDB simple family (application)

EP 90810361 A 19900516; AT 90810361 T 19900516; CH 196089 A 19890525; DE 59001290 T 19900516