

Title (en)

Heavy oil conversion process.

Title (de)

Schwerölkunststoffumwandlungsverfahren.

Title (fr)

Conversion d'huile lourde.

Publication

EP 0400743 B1 19940803 (EN)

Application

EP 90201336 A 19900523

Priority

GB 8912698 A 19890602

Abstract (en)

[origin: EP0400743A1] Process for the conversion of a heavy hydrocarbon oil comprising contacting a hydrocarbon oil which comprises at least 35 %wt of material boiling above 520 DEG C with a hydrogen containing gaseous stream and a catalyst at a temperature of 450-850 DEG C and a hydrogen partial pressure of 10-80 bar, whereby coke-bearing catalyst is withdrawn continuously from the reactor and replaced at least partially by regenerated catalyst.

IPC 1-7

C10G 47/00

IPC 8 full level

C10G 47/00 (2006.01); **C10G 47/12** (2006.01); **C10G 47/30** (2006.01); **C10G 49/04** (2006.01); **C10G 49/16** (2006.01)

CPC (source: EP)

C10G 47/00 (2013.01)

Citation (examination)

Annual Book of ASTM Standards, vol.05.01 (1992), page 99

Cited by

NL1027775C2; US6043288A; USRE38170E; WO2007149913A1; WO9941217A1; WO2007149917A1; WO2007149922A1; EP0488473B1

Designated contracting state (EPC)

BE DE ES FR GB IT NL

DOCDB simple family (publication)

EP 0400743 A1 19901205; EP 0400743 B1 19940803; CA 2018013 A1 19901202; DE 69011217 D1 19940908; DE 69011217 T2 19950126;
ES 2058755 T3 19941101; GB 8912698 D0 19890719; JP H03163194 A 19910715

DOCDB simple family (application)

EP 90201336 A 19900523; CA 2018013 A 19900531; DE 69011217 T 19900523; ES 90201336 T 19900523; GB 8912698 A 19890602;
JP 14014890 A 19900531