

Title (en)

Holding device for a projectile in relation to a telescoped ammunition case.

Title (de)

Vorrichtung zum Halten eines Geschosses in bezug auf das Gehäuse einer teleskopartigen Munition.

Title (fr)

Dispositif de maintien d'un projectile relativement à l'enveloppe d'une munition télescopée.

Publication

EP 0401114 A1 19901205 (FR)

Application

EP 90401448 A 19900531

Priority

FR 8907231 A 19890601

Abstract (en)

The technical field of the invention is that of ammunition of the telescopic type. <??>The invention provide a device for holding a projectile (4) in relation to the casing (2) of an ammunition (1) of the telescopic type, comprising at least one annular ring (3) which is fitted in the casing (2) and in which the projectile (4) is arranged, this holding device being characterised in that it also comprises a cap (10) fitted into the ring (3) and integral with the projectile (4) in the region of the front part of the latter. <??>The invention is used for the production of medium-calibre ammunition.
<IMAGE>

IPC 1-7

F42B 5/045; **F42B 5/184**; **F42B 14/06**

IPC 8 full level

F42B 5/045 (2006.01); **F42B 5/184** (2006.01); **F42B 14/06** (2006.01)

CPC (source: EP US)

F42B 5/045 (2013.01 - EP US); **F42B 5/184** (2013.01 - EP US); **F42B 14/06** (2013.01 - EP US)

Citation (search report)

- [AD] US 3575112 A 19710413 - FARMER LEONARD J
- [AD] GB 1310607 A 19730321 - LUTZ E
- [AD] US 4015527 A 19770405 - EVANS HAROLD O
- [A] EP 0152492 A1 19850828 - RHEINMETALL GMBH [DE]
- [A] FR 2606500 A1 19880513 - SAUVESTRE JEAN CLAUDE [FR]
- [A] FR 2131393 A5 19721110 - OERLIKON BUEHRLE AG

Cited by

FR2725509A1

Designated contracting state (EPC)

BE CH DE GB IT LI NL

DOCDB simple family (publication)

EP 0401114 A1 19901205; **EP 0401114 B1 19930728**; DE 69002402 D1 19930902; DE 69002402 T2 19940113; FR 2647890 A1 19901207; FR 2647890 B1 19940422; US 5163165 A 19921110

DOCDB simple family (application)

EP 90401448 A 19900531; DE 69002402 T 19900531; FR 8907231 A 19890601; US 86347792 A 19920402