

Title (en)

DEVICE FOR POSITIONING A FLEXIBLE PRINTING PLATE ON THE PLATE CYLINDER OF A NOTARY PRINTING MACHINE

Publication

**EP 0401500 A3 19910410 (DE)**

Application

**EP 90107607 A 19900421**

Priority

DE 3918215 A 19890603

Abstract (en)

[origin: JPH0375146A] PURPOSE: To enable rotating of a printing plate on a plate cylinder for register correction without suspending a printing process during mechanical operation by providing a clamping force transmitting element between one of axially fitted levers and a cylinder body and making the element displaceable by an adjusting means. CONSTITUTION: In order to correct a register, both clamping rails 10, 11 are axially fitted to both end parts through each of axially fitted levers 13, 14. The axially fitted levers 13, 14 are pivotally supported, in a reely gyrating manner, by pivotal support pins 15 in a groove 12 formed on a cylinder body 2. In this invention, a clamping force transmitting element, and a flexible rod 27 to the advantage are provided between the axially fitted lever 13 and the cylinder body 2. The flexible rod 27 is displaceable by an adjusting means. In this case, the adjusting means may be a motor 28 for adjustment. Since tensile force to be induced when the flexible rod 27 is displaced is extremely high, it is possible to rotate a printing plate in such a state that the plate is clamped on the cylinder body 2.

IPC 1-7

**B41F 27/12**; **B41F 13/16**

IPC 8 full level

**B41F 13/16** (2006.01); **B41F 27/12** (2006.01)

CPC (source: EP US)

**B41F 13/16** (2013.01 - EP US); **B41F 27/1231** (2013.01 - EP US); **B41P 2227/43** (2013.01 - EP US)

Citation (search report)

[AD] DE 3604209 A1 19870813 - HEIDELBERGER DRUCKMASCH AG [DE]

Cited by

DE102019101172A1; FR2713141A1; EP0507635A1; DE102019120961A1; DE4140022C5; DE4214167A1; GB2254290A; EP3771563A1; DE102020123196A1; WO2022048933A1; US11945210B2

Designated contracting state (EPC)

AT CH DE FR GB IT LI

DOCDB simple family (publication)

**EP 0401500 A2 19901212**; **EP 0401500 A3 19910410**; CA 2018128 A1 19901203; CA 2018128 C 19931005; DE 3918215 C1 19901108; JP H0375146 A 19910329; US 5088409 A 19920218

DOCDB simple family (application)

**EP 90107607 A 19900421**; CA 2018128 A 19900601; DE 3918215 A 19890603; JP 14013190 A 19900531; US 52690290 A 19900521