

Title (en)

Anti-theft case, particularly for compact disc cassettes, video cassettes, and the like.

Title (de)

Diebstahlsicherungsgehäuse, insbesondere für CD-Kassetten, Videokassetten und ähnliches.

Title (fr)

Boîte antivol, en particulier pour cassettes CD, cassettes vidéo et similiaires.

Publication

EP 0402822 A2 19901219 (EN)

Application

EP 90110980 A 19900611

Priority

IT 170889 A 19890614

Abstract (en)

An anti-theft case, particularly for compact discs, music cassettes, video cassettes, and the like, is provided with movable means (7, 7 min) for locking a cassette (15) within such a case. According to the invention, the case comprises a box (1) having substantially a parallelepipedal shape, and being provided with an opening (2) for a cassette to be inserted therethrough into its box, which is formed in at least one of the box sides, in such a manner as to leave at least two wall portions (3, 4) which extend from two opposite end-side walls (5, 6) of box (1), and which are longer than the extent of cassette (15) in the direction in which a cassette is inserted into its box. A movable abutment member (7, 7 min) is provided in the region of one of the two end-side wall portions (3, 4) of the box sides, and is caused to cooperate with one end-side edge of cassette (15), the said movable abutment member (7, 7 min) being pushed by spring means (10, 10 min) into its abutting active position, or vice-versa. By a locking and unlocking device (11) the movable abutment member (7, 7 min) is moved from the said abutting active position into a withdrawn inactive position. The cassette (15) is inserted into its case in an inclined condition, and with the movable abutment member (7, 7 min) in its inactive position, the cassette is so shifted as to be engaged under the end-side wall portion (4) which is associated with the movable abutment member (7, 7 min), by being passed thereover, whereupon the cassette (15) is moved backward so as to be engaged also under the opposite end-side wall portion (3), thus uncovering the movable abutment member (7, 7 min) which is moved into its active position, in which it is caused to cooperate with the associated end-side edge of cassette (15), whereby any such shiftement of cassette (15) is prevented, that may be apt to disengage the same for the two end-side wall portions (3, 4).

IPC 1-7

A47F 3/00; E05B 73/00; G08B 13/24; G11B 33/04

IPC 8 full level

E05B 73/00 (2006.01)

CPC (source: EP)

E05B 73/0023 (2013.01)

Cited by

US5806694A; US6155087A; EP0935570A4; EP0807735A3; FR2751457A1; FR2773696A1; EP0729897A4; US5769218A; FR2862999A1; FR2704592A1; ES2272142A1; EP0744520A3; AU649808B2; EP0811740A3; CN111414517A; US7325678B2; WO9526546A3; WO9836143A1; WO2005056958A1; WO9315294A1; WO2013044572A1; WO9218035A1; WO9936652A1; WO9939068A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0402822 A2 19901219; EP 0402822 A3 19920909; EP 0402822 B1 19941207; EP 0402822 B2 19981007; AT E115325 T1 19941215; DE 69014722 D1 19950119; DE 69014722 T2 19950601; DE 69014722 T3 19990506; DK 0402822 T3 19950206; DK 0402822 T4 19990621; ES 2066910 T3 19950316; ES 2066910 T5 19990201; HK 123697 A 19970912; IT 1235362 B 19920630; IT 8901708 A0 19890614

DOCDB simple family (application)

EP 90110980 A 19900611; AT 90110980 T 19900611; DE 69014722 T 19900611; DK 90110980 T 19900611; ES 90110980 T 19900611; HK 123697 A 19970626; IT 170889 A 19890614