

Title (en)

Actuating handle.

Title (de)

Betätigungshandhabe.

Title (fr)

Poignée de commande.

Publication

**EP 0403868 B1 19940504 (DE)**

Application

**EP 90110539 A 19900602**

Priority

DE 8907691 U 19890623

Abstract (en)

[origin: EP0403868A2] A lockable window grip (10) has as a lock a spring-loaded profile cylinder (60) in a grip head (14) which is mounted on a stop plate (40) axially fixedly, but rotatably. Supported resiliently on it or on a cover plate (48) is a locking piece (58), in particular a rotationally symmetrical claw ring. A flanged bush (22) is integral with a cap plate (24) having a receptacle (30), inclined at the angle (  $\alpha$  ), for the lock detent member (70) which, for example, is a slide guided slideably in the grip head (14) and possessing two legs (26) with oblique press-down ends (78) on both sides of a collar (72). A U- shaped retaining spring (64) is supported on a slope (34) of the cap plate (24) which has a projection (84) for a lock-actuable spring element (90) and inside which the locking piece (38) can slide on a spacer ring (36). The lock (60) is vertically displaceable and fixable in the grip head (14) at its angle of inclination (  $\alpha$  ) relative to the axis of rotation (A), its outer face being approximately flush with the inclined grip-head cover surface (16) in the locked state. <IMAGE>

IPC 1-7

**E05B 13/10**

IPC 8 full level

**E05B 13/10** (2006.01)

CPC (source: EP)

**E05B 13/106** (2013.01)

Cited by

US6546765B1

Designated contracting state (EPC)

AT CH DE FR GB IT LI NL

DOCDB simple family (publication)

**EP 0403868 A2 19901227; EP 0403868 A3 19910821; EP 0403868 B1 19940504**; AT E105362 T1 19940515; DE 59005589 D1 19940609; DE 8907691 U1 19890824

DOCDB simple family (application)

**EP 90110539 A 19900602**; AT 90110539 T 19900602; DE 59005589 T 19900602; DE 8907691 U 19890623