

Title (en)
LOW PROFILE DETECTOR WITH MULTI-SIDED SOURCE

Publication
EP 0405473 A3 19910502 (EN)

Application
EP 90112170 A 19900626

Priority
• US 37315689 A 19890628
• US 53507190 A 19900612

Abstract (en)
[origin: EP0405473A2] A low profile ionization type smoke sensor (50) is formed with a cylindrical housing (62) having a diameter on the order of 50.8 mm with a height on the order of 25.4 mm or less. A common electrode (66) is centrally located within the housing (62). A single sided ion source (74) is carried on the common electrode (66) and centrally located thereon. The ion source (74) extends into a first or reference region (68b) and into a second or active region (68a). First and second target electrodes (70, 72) are provided , attached to the housing (66), in each region (68a, 68b). The ion source (74) emits particles on paths that are substantially parallel to the common electrode (66). A 25.4 mm path, substantially parallel to the common electrode (66), is provided between the ion source (74) and each target electrode (70, 72).

IPC 1-7
G08B 17/113

IPC 8 full level
G08B 17/11 (2006.01); **G08B 17/113** (2006.01)

CPC (source: EP)
G08B 17/11 (2013.01); **G08B 17/113** (2013.01)

Citation (search report)
• [A] FR 2224819 A1 19741031 - CERBERUS AG [CH]
• [A] US 4327289 A 19820427 - SOLOMON ELIAS E
• [A] EP 0121048 A1 19841010 - CERBERUS AG [CH]

Cited by
CN111402540A; US11961378B2

Designated contracting state (EPC)
BE DE FR GB IT

DOCDB simple family (publication)
EP 0405473 A2 19910102; EP 0405473 A3 19910502

DOCDB simple family (application)
EP 90112170 A 19900626